

User Guide - COMe-bID7 (E2)

Rev 1.7



This page has been intentionally left blank

User Guide - COMe-bID7 (E2)

Disclaimer

JUMPttec would like to point out that the information contained in this user guide may be subject to alteration, particularly as a result of the constant upgrading of JUMPttec products. This document does not entail any guarantee on the part of JUMPttec with respect to technical processes described in the user guide or any product characteristics set out in the user guide. JUMPttec assumes no responsibility or liability for the use of the described product(s), conveys no license or title under any patent, copyright or mask work rights to these products and makes no representations or warranties that these products are free from patent, copyright or mask work right infringement unless otherwise specified. Applications that are described in this user guide are for illustration purposes only. JUMPttec makes no representation or warranty that such application will be suitable for the specified use without further testing or modification. JUMPttec expressly informs the user that this user guide only contains a general description of processes and instructions which may not be applicable in every individual case. In cases of doubt, please contact JUMPttec.

This user guide is protected by copyright. All rights are reserved by JUMPttec. No part of this document may be reproduced, transmitted, transcribed, stored in a retrieval system, or translated into any language or computer language, in any form or by any means (electronic, mechanical, photocopying, recording, or otherwise), without the express written permission of JUMPttec. JUMPttec points out that the information contained in this user guide is constantly being updated in line with the technical alterations and improvements made by JUMPttec to the products and thus this user guide only reflects the technical status of the products by JUMPttec at the time of publishing.

Brand and product names are trademarks or registered trademarks of their respective owners.

©2025 by JUMPttec GmbH

JUMPttec GmbH

Brunnwiesenstrasse 16

94469 Deggendorf

Germany

www.congatec.com

Intended Use

This device and associated software are not designed, manufactured or intended for use or resale for the operation of nuclear facilities, the navigation, control or communication systems for aircraft or other transportation, air traffic control, life support or life sustaining applications, weapons systems, or any other application in a hazardous environment, or requiring fail-safe performance, or in which the failure of products could lead directly to death, personal injury, or severe physical or environmental damage (collectively, “high risk applications”).

You understand and agree that your use of JUMPtec devices as a component in High Risk Applications is entirely at your risk. To minimize the risks associated with your products and applications, you should provide adequate design and operating safeguards. You are solely responsible for compliance with all legal, regulatory, safety, and security related requirements concerning your products. You are responsible to ensure that your systems (and any JUMPtec hardware or software components incorporated in your systems) meet all applicable requirements. Unless otherwise stated in the product documentation, the JUMPtec device is not provided with error-tolerance capabilities and cannot therefore be deemed as being engineered, manufactured or setup to be compliant for implementation or for resale as device in High Risk Applications. All application and safety related information in this document (including application descriptions, suggested safety measures, suggested JUMPtec products, and other materials) is provided for reference only.

NOTICE

You find the most recent version of the “General Safety Instructions“ online in the download area of this product on our [JUMPtec website](#).

NOTICE

This product is not intended for use or suited for storage or operation in corrosive environments, in particular under exposure to sulfur and chlorine and their compounds. For information on how to harden electronics and mechanics against these stress conditions, contact JUMPtec Support.

Revision History

Revision	Brief Description of Changes	Date of Issue	Author
1.0	Release	2023-January-24	ih
1.1	Added chapter 3.12	2023-February-08	ih
1.2	New Kontron logo	2023-March-29	ih
1.3	UART option removed	2023-April-19	ih
1.4	Updated chapter 6.5 / 6.6	2023-August-31	ih
1.41	Minor enhancements regarding chapter 6.5 / 6.6	2023-September-18	ih
1.5	Corrected memory P/N, added modified signal names for GBEO changed with COM.0 Rev3.1	2023-November-24	ih
1.6	Extended CPU-list with IceLake-D refresh SKUs	2024-February-16	ih
1.7	Updated block diagram - JUMPtec	2025-July-22	ih

Terms and Conditions

JUMPtec warrants products in accordance with defined regional warranty periods. For more information about warranty compliance and conformity, and the warranty period in your region, visit <https://www.congatec.com/en/terms-and-conditions>.

JUMPtec sells products worldwide and declares regional General Terms & Conditions of Sale, and Purchase Order Terms & Conditions. Visit <https://www.congatec.com/en/terms-and-conditions>.

For contact information, refer to the corporate offices contact information on the last page of this user guide or visit our website [CONTACT US](#).

Customer Support

Find JUMPtec contacts by visiting <https://www.congatec.com/en/service-support>.

Customer Service

As a trusted technology innovator and global solutions provider, JUMPtec extends its embedded market strengths into a services portfolio allowing companies to break the barriers of traditional product lifecycles. Proven product expertise coupled with collaborative and highly-experienced support enables JUMPtec to provide exceptional peace of mind to build and maintain successful products.

For more details on JUMPtec’s service offerings such as: enhanced repair services, extended warranty, JUMPtec training academy, and more visit <https://www.congatec.com/en/service-support>.

Customer Comments

If you have any difficulties using this user guide, discover an error, or just want to provide some feedback, contact [JUMPtec Support](#). Detail any errors you find. We will correct the errors or problems as soon as possible and post the revised user guide on our website.

Symbols

The following symbols may be used in this user guide



DANGER indicates a hazardous situation which, if not avoided, will result in death or serious injury.



WARNING indicates a hazardous situation which, if not avoided, could result in death or serious injury.



NOTICE indicates a property damage message.



CAUTION indicates a hazardous situation which, if not avoided, may result in minor or moderate injury
ATTENTION indique une situation dangereuse qui, si elle n'est pas évitée, peut entraîner des blessures mineures ou modérées.



Electric Shock!

This symbol and title warn of hazards due to electrical shocks (> 60 V) when touching products or parts of products. Failure to observe the precautions indicated and/or prescribed by the law may endanger your life/health and/or result in damage to your material.



ESD Sensitive Device!

This symbol and title inform that the electronic boards and their components are sensitive to static electricity. Care must therefore be taken during all handling operations and inspections of this product in order to ensure product integrity at all times.



Caution: HOT Surface!

Do NOT touch! Allow to cool before servicing.

Attention : Surface CHAUDE !

Ne pas toucher ! Laissez refroidir avant de procéder à l'entretien.



Caution: Laser!

This symbol inform of the risk of exposure to laser beam and light emitting devices (LEDs) from an electrical device. Eye protection per manufacturer notice shall review before servicing.



This symbol indicates general information about the product and the user guide.
This symbol also indicates detail information about the specific product configuration.



This symbol precedes helpful hints and tips for daily use.

For Your Safety

Your new JUMPtec product was developed and tested carefully to provide all features necessary to ensure its compliance with electrical safety requirements. It was also designed for a long fault-free life. However, the life expectancy of your product can be drastically reduced by improper treatment during unpacking and installation. Therefore, in the interest of your own safety and of the correct operation of your new JUMPtec product, you are requested to conform with the following guidelines.

High Voltage Safety Instructions

As a precaution and in case of danger, the power connector must be easily accessible. The power connector is the product's main disconnect device.

CAUTION

Warning

All operations on this product must be carried out by sufficiently skilled personnel only.

CAUTION

Electric Shock!



Before installing a non hot-swappable JUMPtec product into a system always ensure that your mains power is switched off. This also applies to the installation of piggybacks. Serious electrical shock hazards can exist during all installation, repair, and maintenance operations on this product. Therefore, always unplug the power cable and any other cables which provide external voltages before performing any work on this product.

Earth ground connection to vehicle's chassis or a central grounding point shall remain connected. The earth ground cable shall be the last cable to be disconnected or the first cable to be connected when performing installation or removal procedures on this product.

Special Handling and Unpacking Instruction

NOTICE

ESD Sensitive Device!



Electronic boards and their components are sensitive to static electricity. Therefore, care must be taken during all handling operations and inspections of this product, in order to ensure product integrity at all times.

CAUTION

Handling and operation of the product is permitted only for trained personnel within a work place that is access controlled. Follow the "General Safety Instructions" supplied with the product.

Do not handle this product out of its protective enclosure while it is not used for operational purposes unless it is otherwise protected.

Whenever possible, unpack or pack this product only at EOS/ESD safe work stations. Where a safe work station is not guaranteed, it is important for the user to be electrically discharged before touching the product with his/her hands or tools. This is most easily done by touching a metal part of your system housing.

It is particularly important to observe standard anti-static precautions when changing piggybacks, ROM devices, jumper settings etc. If the product contains batteries for RTC or memory backup, ensure that the product is not placed on conductive surfaces, including anti-static plastics or sponges. They can cause short circuits and damage the batteries or conductive circuits on the product.

Lithium Battery Precautions

If your product is equipped with a lithium battery, take the following precautions when replacing the lithium battery.

⚠ CAUTION

Risk of Explosion if the lithium Battery is replaced by an incorrect Type. Dispose of used lithium batteries According to the instructions.

Risque d'explosion si la pile au lithium est remplacée par une pile de type incorrect.
Éliminez les piles au lithium usagées conformément aux instructions.

General Instructions on Usage

In order to maintain JUMPtec's product warranty, this product must not be altered or modified in any way. Changes or modifications to the product, that are not explicitly approved by JUMPtec and described in this user guide or received from [JUMPtec Support](#) as a special handling instruction, will void your warranty.

This product should only be installed in or connected to systems that fulfill all necessary technical and specific environmental requirements. This also applies to the operational temperature range of the specific board version that must not be exceeded. If batteries are present, their temperature restrictions must be taken into account.

In performing all necessary installation and application operations, only follow the instructions supplied by the present user guide.

Keep all the original packaging material for future storage or warranty shipments. If it is necessary to store or ship the product then re-pack it in the same manner as it was delivered.

Special care is necessary when handling or unpacking the product. See Special Handling and Unpacking Instruction.

Quality and Environmental Management

JUMPTec aims to deliver reliable high-end products designed and built for quality, and aims to complying with environmental laws, regulations, and other environmentally oriented requirements. For more information regarding JUMPTec's quality and environmental responsibilities, visit <https://www.congatec.com/en/about-jumpte/quality>.

Disposal and Recycling

JUMPTec's products are manufactured to satisfy environmental protection requirements where possible. Many of the components used are capable of being recycled. Final disposal of this product after its service life must be accomplished in accordance with applicable country, state, or local laws or regulations.

WEEE Compliance

The Waste Electrical and Electronic Equipment (WEEE) Directive aims to:

- ▶ Reduce waste arising from electrical and electronic equipment (EEE)
- ▶ Make producers of EEE responsible for the environmental impact of their products, especially when the product become waste
- ▶ Encourage separate collection and subsequent treatment, reuse, recovery, recycling and sound environmental disposal of EEE
- ▶ Improve the environmental performance of all those involved during the lifecycle of EEE



Environmental protection is a high priority with JUMPTec.

JUMPTec follows the WEEE directive

You are encouraged to return our products for proper disposal.

Table of Contents

Revision History.....	5
Terms and Conditions	5
Customer Support	5
Customer Service	5
Customer Comments	5
Symbols	6
For Your Safety	8
High Voltage Safety Instructions	8
Special Handling and Unpacking Instruction.....	8
Lithium Battery Precautions.....	9
General Instructions on Usage	9
Quality and Environmental Management.....	10
Disposal and Recycling	10
WEEE Compliance	10
Table of Contents	11
List of Tables.....	13
List of Figures	14
1/ Introduction	15
1.1. Product Description.....	15
1.2. Product Naming Clarification	15
1.3. Understanding COM Express® Functionality.....	16
1.4. COM Express® Documentation	16
1.5. COM Express® Benefits	16
2/ Product Specification	17
2.1. Module Definition	17
2.2. Commercial Grade Modules.....	17
2.3. Industrial Grade Modules.....	17
2.4. Product Views	18
3/ Functional Specification	20
3.1. Block Diagram COMe-bID7.....	20
3.2. Processors	21
3.3. COM Express Compliance.....	22
3.3.1. COM.0 Rev 3.1: default configuration:.....	22
3.3.2. COM.0 Rev 3.0: available on request (legacy mode).....	23
3.4. Memory.....	23
3.5. PCI Express 4.0	24
3.6. HSIO Usage	24
3.7. USB	27
3.8. SATA	28
3.9. Ethernet – 1G / 2.5GBASE-T LAN.....	28
3.10. Ethernet – 4x 10GBASE-KR.....	28

3.10.1. 10G LAN CEI mode (default configuration): 28

3.10.2. 10G LAN Legacy mode (available on request):..... 28

3.10.3. Overview of currently supported LAN Interfaces on COMe-bID7 29

3.11. UART..... 31

3.12. Additional Features 31

3.13. Evaluation platforms for COMe-bID7 – Compatibility Matrix 32

4/ Features and Interfaces 33

4.1. ACPI Suspend Modes and Resume Events 33

4.2. Real Time Clock (RTC)..... 33

4.3. NVMe Storage (Option)..... 33

4.4. Hardware Monitor (HWM)..... 33

4.5. Trusted Platform Module (TPM) 33

4.6. Onboard Fan Connector 34

4.7. Watchdog Timer (WDT) Dual Stage..... 34

4.8. Watchdog Timer Signal 34

4.9. Hyper-Threading 35

4.10. Fast I2C 35

4.11. LPC..... 35

4.12. Serial Peripheral Interface (SPI)..... 35

4.12.1. SPI Boot 35

4.12.2. SPI Flash Update..... 36

4.13. System Management Bus (SMB) 36

4.14. GPIO 37

4.15. NS-CI..... 37

5/ Accessories..... 38

5.1. Product Specific Accessories 38

5.2. General Accessories 39

6/ Electrical Specification 40

6.1. Supply Voltage..... 40

6.2. Power Supply Rise Time 40

6.3. Supply Voltage Ripple..... 40

6.4. Power Consumption 40

6.5. ATX Mode..... 41

6.6. Single Supply Mode..... 41

7/ Power Control 43

7.1. Power Supply..... 43

7.2. Power Supply Control Settings 43

8/ Standards and Certification 44

8.1. MTBF 45

9/ Mechanical Specification 46

9.1. Dimensions..... 46

9.1.1. Height 47

9.1.2. Module Height with Four SODIMM Memory Sockets..... 47

9.2. Thermal Management, Heatspreader and Cooling Solutions 49

9.2.1. Heatspreader Dimensions 50

10/ COME Connector Pin-out List 52

11/ UEFI BIOS 71

11.1. Starting the UEFI BIOS 71

11.2. Navigating the UEFI BIOS 71

11.3. Setup Menus 72

11.4. Getting Help 72

11.5. UEFI Shell..... 72

11.5.1. Entering the UEFI Shell 73

11.5.2. Exiting the UEFI Shell..... 73

11.6. UEFI Shell Scripting..... 73

11.6.1. Startup Scripting..... 73

11.6.2. Create a Startup Script 74

11.6.3. Example of Startup Scripts 74

11.7. Firmware Update 74

12/ Technical Support 75

12.1. Warranty 75

12.2. Returning Defective Merchandise..... 75

13/ Storage and Transportation 77

13.1. Storage 77

13.2. Transportation..... 77

Appendix: Terminology 78

List of Tables

Table 1: Pin Assignment of Type 7 and COMe-bID7..... 16

Table 2: Commercial Grade Modules (0°C to 60°C operating) 17

Table 3: Industrial Grade Modules by Design (E2, -40°C up to 85°C Operating)..... 17

Table 4: Intel® Processor D-1700/D-1800 Product Family Specifications 21

Table 5: COM Express Compliance..... 22

Table 6: Memory Features 23

Table 7: SoC – PCI Express Gen. 4.0 24

Table 8: SoC – HSIO Usage: PCI Express Gen 3.0, SATA, USB, onboard I/O 26

Table 9: BIOS versions 27

Table 10: Supported USB Features..... 28

Table 11: General, Special and Optional Features 31

Table 12: Onboard Fan Connector 34

Table 13: Dual Staged Watchdog Timer- Time-Out Events 34

Table 14: I2C Bus Port Address 35

Table 15: SPI Boot Pin Configuration 36

Table 16: Supported SPI Boot Flash 36

Table 17: SMBus Address 37

Table 18: Product Specific Accessories List 38

Table 19: Cooler and Heatspreader 38

Table 20: General Accessories List 39

Table 21: Memory Modules 39

Table 22: COM Express® Connector Electrical Specifications 40

Table 23: ATX Mode 41

Table 24: Single Supply Mode	41
Table 25: Power Supply Control Settings	43
Table 26: Standards and Certification Compliance	44
Table 27: Pin-out List A.....	53
Table 28: Pin-out List B.....	56
Table 29: Pin-out List C.....	61
Table 30: Pin-out List D	65
Table 31: Summary – COM.0 REV3.1 vs REV3.0.....	68
Table 39: Navigation Hot Keys Available in the Legend Bar.....	71

List of Figures

Figure 1: Top View of COMe-bID7.....	18
Figure 2: Bottom View of COMe-bID7.....	19
Figure 3: Block Diagram COMe-bID7.....	20
Figure 4: MTBF De-rating Values (Reliability report: COMe-bID7 E2 D-1747NTE EV).....	45
Figure 5: Module Dimensions	46
Figure 6: Module Height.....	47
Figure 7: Module Top and Bottom SODIMM Assembly (Option).....	48
Figure 8: Heatspreader 68009-0000-99-0 Dimensions	50
Figure 9: Heatspreader 68009-0000-99-1 Dimensions	50
Figure 10: COMe Connector with 220 pins	52
Figure 11: COMe Connector Pinout	52
Figure 7: Setup Menu Selection Bar.....	72

1/ Introduction

1.1. Product Description

JUMPttec 's Computer-on-Module COMe-bID7 is a COM Express® BASIC TYPE 7 form-factor with Intel®'s Xeon® D-1700/D-1800 processor family. The Intel® Xeon® D-1700/D-1800 Generation increases efficiency and performance per watt ratio, which is a result of the innovative 10nm technology and has up to 10 cores for control, micro server, storage and communication applications in Internet of Things (IoT) and embedded environment. The COMe-bID7 is also designed for industrial temperature environment.

- ▶ Intel® Xeon® Processor D-1700/D-1800 System on Chip (SoC), member of the Intel® Xeon® Processor family
- ▶ DDR4 memory technology up to 128 GByte ECC with 4x SODIMM sockets
- ▶ High-speed connectivity 16x PCIe Gen4 + 16x PCIe Gen3
- ▶ Quad 10 GbE interfaces

1.2. Product Naming Clarification

COM Express® defines a Computer-on-Module, or COM, with all the components necessary for a bootable host computer, packaged as a super component. The product name for JUMPttec COM Express® Computer-On-Modules consists of:

Industry standard short form

- ▶ COMe-

Module form factor

- ▶ b=basic (125mm x 95mm)
- ▶ c=compact (95mm x 95mm)
- ▶ m=mini (84mm x 55mm)

Intel's processor code name

- ▶ ID = Ice Lake-D

Pinout type

- ▶ 7 = Type 7

Available temperature variants

- ▶ Commercial
- ▶ E2 = Industrial

Processor Identifier

- ▶ Chipset identifier (if chipset assembled)

Storage

- ▶ NVMe (if assembled)

1.3. Understanding COM Express® Functionality

All COM Express® basic and compact modules contain two 220pin connectors; each of it has two rows called Row A & B on primary connector and Row C & D on secondary connector. The COM Express® Computer-On-Module (COM) features the following maximum amount of interfaces according to the PCI Industrial Computer Manufacturers Group (PICMG) module Pin-out type.

Table 1: Pin Assignment of Type 7 and COMe-bID7

Feature	Type 7 Standard	COMe-bID7 Pinout
NBASE-T LAN	1x 10GBit max.	1x 2.5GBit max
10GBASE-KR LAN Ports	4x	4x
NC-SI	1x	1x
PCI Express	32x	16x PCIe Gen3 16x PCIe Gen4
Serial ATA	2x	2x
USB	4x USB 3.2 (USB 2.0)	4x USB 3.1 Gen1 respect. USB 3.0 (USB 2.0)
Serial Ports	2x	2x
eSPI/LPC	1x	1x
External SPI	1x	1x
External SMB	1x	1x
External I2C	1x	1x
GPIO	8x	8x

1.4. COM Express® Documentation

The COM Express® Specification defines the COM Express® module form factor, pin-out, and signals. This specification is available at the PICMG® website by filling out the order form.

1.5. COM Express® Benefits

COM Express® defines a Computer-On-Module, or COM, with all the components necessary for a bootable host computer, packaged as a highly integrated computer. All COM Express® modules are very compact and feature a standardized form factor and a standardized connector layout that carry a specified set of signals. Each COM is based on the COM Express® specification. This standardization allows designers to create a single-system baseboard that can accept present and future COM Express® modules.

The baseboard designer can optimize exactly how each of these functions implements physically. Designers can place connectors precisely where needed for the application, on a baseboard optimally designed to fit a system's packaging.

A single baseboard design can use a range of COM Express® modules with different sizes and pinouts. This flexibility differentiates products at various price and performance points and provides a built-in upgrade path when designing future-proof systems. The modularity of a COM Express® solution also ensures against obsolescence when computer technology evolves. A properly designed COM Express® baseboard can work with several successive generations of COM Express® modules.

A COM Express® baseboard design has many advantages of a customized computer-board design and, additionally, delivers better obsolescence protection, heavily reduced engineering effort, and faster time to market.

2/ Product Specification

2.1. Module Definition

The COM Express® basic sized Computer-on-Module COMe-bID7 follows pin-out Type 7 and is compatible to the PICMG specification COM.0 Rev 3.1.

The COMe-bID7 can also be offered compliant to COM-Express Spec Rev 3.0 on request.

The COMe-bID7 is available in different variants to cover the individual demands in performance, price and power.

2.2. Commercial Grade Modules

The following is a list of modules for commercial temperature range.

Table 2: Commercial Grade Modules (0°C to 60°C operating)

Product Number	Product Name	Description
68008-0000-49-2	COMe-bID7 D-1749NT	COM Express® basic pin-out type 7 COM.0 R3.1 with Intel® D-1749NT, 90 W, 10 core, 3.0 GHz, 4x 10GBASE-KR, 16x PCIe Gen4, 16x PCIe Gen3, 2x DDR4 SO-DIMM socket
68008-0000-35-1	COMe-bID7 D-1735TR	COM Express® basic pin-out type 7 COM.0 R3.1 with Intel® D-1735TR, 59 W, 8 core, 2.2 GHz, 4x 10GBASE-KR, 4x 10GBASE-KR, 16x PCIe Gen4, 16x PCIe Gen3, 2x DDR4 SO-DIMM socket
68008-0000-12-1	COMe-bID7 D-1712TR	COM Express® COM.0 R3.1 basic pin-out type 7 with Intel® D-1712TR, 40 W, 4 core, 2.0 GHz, 4x 10GBASE-KR, 16x PCIe Gen4, 16x PCIe Gen3, 2x DDR4 SO-DIMM socket

2.3. Industrial Grade Modules


Industrial temperature grade modules are available based on their design. Please contact your local sales or support for further details.

Table 3: Industrial Grade Modules by Design (E2, -40°C up to 85°C Operating)

Product Number	Product Name	Description
68009-0000-46-1	COMe-bID7 E2 D-1746TER	COM Express® basic pin-out type 7 COM.0 R3.1 with Intel® D-1746TER, 67/56 W, 10 core, 2.0 GHz, 4x 10GBASE-KR, 16x PCIe Gen4, 16x PCIe Gen3, 2x DDR4 SO-DIMM socket, industrial temperature
68009-0000-32-1	COMe-bID7 E2 D-1732TE	COM Express® basic pin-out type 7 COM.0 R3.1 with Intel® D-1732TE, 52 W, 8 core, 1.9 GHz, 4x 10GBASE-KR, 16x PCIe Gen4, 16x PCIe Gen3, 2x DDR4 SO-DIMM socket, industrial temperature
68009-0000-15-1	COMe-bID7 E2 D-1715TER	COM Express® basic pin-out type 7 COM.0 R3.1 with Intel® D-1715TER, 50 W, 4 core, 2.4 GHz, 4x 10GBASE-KR, 16x PCIe Gen4, 16x PCIe Gen3, 2x DDR4 SO-DIMM socket, industrial temperature


2.4. Product Views

Figure 1: Top View of COMe-BID7



1. Fan Connector
2. Processor
3. 2x DDR4 SODIMM sockets
4. Optional NVMe

Figure 2: Bottom View of COMe-bID7



- 5. XDP debug port (not populated on production units)
- 6. Optional 2x DDR4 SODIMM sockets
- 7. 2x COMe connectors

3.2. Processors

The Intel® Xeon® processor D-1700/D-1800 processor family with 45 mm x 45 mm package size (FCBGA) is the next generation System-on-Chip (SoC) with processor cores built using Intel 10-nanometer process technology. The three major complexes in this highly-integrated SoC are the CPU, PCH and NAC. The Central Processing Unit (CPU) complex contains up to 10 next-generation 64-bit processor cores.

The Platform Controller Hub (PCH) of the SoC is architected with a rich set of interconnect technologies.

The Network Accelerator Complex (NAC) includes technologies for security and packet processing.

The SoC architecture is highly scalable and efficient, providing a unified solution across an array of products. The processor SKUs are targeted for long life supply availability with extended reliability in communications environments.

Table 4: Intel® Processor D-1700/D-1800 Product Family Specifications

Intel SKU	SKU	Group	TDP (W)	No. of Cores	IOTG	E-Tmp	Tcase min (°C)	DDR Freq. (MHz)	Base Freq. (GHz)	All/Max Turbo (GHz)	BW LAN (GbE)	BW QAT (GbE)
D-1746TER	std	NIC	67/56	10	Yes	Yes	-40	2667	2.0	2.5/3.1	100G	OFF
D-1848TER	req	NIC	57	10	Yes	Yes	-40	2667	2.0	2.5/3.1	100G	OFF
D-1749NT	std	QAT	90	10	No	No	0	2667	3.0	3.5/3.5	100G	20G
D-1748TE	req	NIC	65	10	No	Yes	-40	2400	2.3	2.8/3.4	50G	OFF
D-1747NTE	std	QAT	80	10	No	Yes	-40	2933	2.5	3.0/3.5	100G	20G
D-1844NT	std	QAT	55	10	No	No	0	2667	2.0	2.6/3.1	50G	20G
D-1735TR	std	NIC	59	8	Yes	No	0	2933	2.2	2.7/3.4	50G	OFF
D-1732TE	std	NIC	52	8	Yes	Yes	-40	2667	1.9	2.4/3.0	50G	OFF
D-1734NT	req	QAT	50	8	No	No	0	2667	2.0	2.5/3.1	50G	20G
D-1736NT	req	QAT	67	8	No	No	0	2667	2.7	3.2/3.5	50G	20G
D-1733NT	req	QAT	53	8	No	No	0	2400	2.0	2.5/3.1	50G	20G
D-1823NT	req	QAT	55	6	No	No	0	2400	2.8	3.3/3.5	50G	10G
D-1715TER	std	NIC	50	4	Yes	Yes	-40	2667	2.4	2.9/3.5	50G	OFF
D-1712TR	std	NIC	40	4	Yes	No	0	2400	2.0	2.5/3.1	50G	OFF
D-1718T	std	NIC	46	4	No	No	0	2933	2.6	3.1/3.5	50G	OFF
D-1713NT	req	QAT	45	4	No	No	0	2400	2.2	2.9/3.5	50G	10G

D-1713NTE	req	QAT	45	4	No	Yes	-40	2400	2.2	2.7/ 3.3	50G	10G
D-1813NT	req	QAT	42	4	No	No	0	2400	2.2	2.4/ 2.4	50G	10G
D-1846	req	Comp.	55	10	No	No	0	2933	2.0	2.6/ 3.1	0G	OFF
D-1739	req	Comp.	83	8	No	No	0	2933	3.0	3.5/ 3.5	0G	OFF
D-1736	req	Comp.	55	8	No	No	0	2933	2.3	2.8/ 3.4	0G	OFF
D-1834	req	Comp.	42	8	No	No	0	2667	1.8	2.4/ 2.9	0G	OFF
D-1726	req	Comp.	70	6	No	No	0	2933	2.9	3.4/ 3.5	0G	OFF
D-1722NE	req	Comp.	36	6	No	Yes	-40	2400	1.7	2.1/ 2.7	0G	OFF
D-1714	req	Comp.	38	4	No	No	0	2667	2.3	2.8/ 3.4	0G	OFF
D1702	req	Comp.	25	2	No	No	0	2400	1.6	1.7/ 1.7	0G	OFF



DTR (Dynamic Temperature Range) limits apply. The behavior is described in Intel document #595914

3.3. COM Express Compliance

The COMe-bID7 can be offered in two different versions regarding the compliance to the COM Express COM.0 specification Rev 3.0 or Rev 3.1.

The main different between both is the support of PCIe Gen 4.0 and the pin definition for the 10G LAN interfaces

Table 5: COM Express Compliance

	PCI Express	10G Ethernet
COM.0 Rev 3.1 (default)	PCIe Gen 4.0 on COMe PCIe #16-31 2nd PCIe Clk to carrier	CEI-mode (see chapter 3.10)
COM.0 Rev 3.0 (on request)	PCIe Gen 3.0 on COMe PCIe #16-31	Legacy mode (see chapter 3.10)

3.3.1. COM.0 Rev 3.1: default configuration:

10G LAN - CEI (Common Electrical Interface) mode

This mode is used on COMe-bID7 modules for carriers/backplanes designed according to the COM Express specification COM.0 Rev 3.1 and newer. In comparison to the legacy mode the CEI mode consists of a fewer set of

signals between module and carrier/backplane. Additional components required for a particular Ethernet mode – such as LED controller, etc.. - are populated on the carrier/backplane

PCI Express Gen4 support

The COMe PCIe #0-15 from the SOC-PCH hosts PCIe Gen3 root devices and provides the necessary clock.

The COMe PCIe #16-31 from the CPU hosts PCIe Gen4 root devices, but needs a high accuracy external clock source. The additional clock source provides the reference clock to the CPU and also to the Carrier board PCIe Gen4 target, over the 2nd set of PCIe clock reference pins provided in COM.0 Rev 3.1.

3.3.2. COM.0 Rev 3.0: available on request (legacy mode)

10G LAN - "legacy" mode

For selected 10GbE modes the required additional components are directly populated on the COMe-bID7 module. The legacy mode enables those components on the module, which allow using the COMe-bID7 module on carriers/backplanes designed according to the COM Express specification COM.0 Rev 3.0.

PCI Express Gen3 support

There is a single 100 MHz PCI Express reference clock delivered over the COM Express connector.

3.4. Memory

Up to 4x SODIMM Socket DDR4 non-ECC/ECC, height: 4+8mm

2x SODIMM sockets on top side – max. DDR4-2933 MT/s (depends on the processor SKU)

Optional additional 2x SODIMM sockets on the bottom side (this is out of the PICMG specification) – max. DDR4-2666 MT/s (depends on the processor SKU)



Second SO-DIMM (bottom side of module) exceeds the maximum height for COM Express modules defined by the PICMG specification between carrier and module, even with an 8mm connector stack-up. Special care has to be taken for the Carrier Board design – a cut-out area is recommended.

Table 6: Memory Features

Socket	Default: 2x DDR4 SO-DIMM On request: 4x DDR4 SODIMM
Memory Type	DDR4, up to 2933 MT/s, up to 32 GB per socket
Memory Module Capacity	8, 16 and 32 GB

3.5. PCI Express 4.0

The SoC CPU supports 16x PCIe Gen 4.0 lanes supporting COMe PCIe lanes #16-31 with one Root Complex (RPC) and four Root Ports (RP).

Minimum PCIe link support per Root Port is x4 lanes, however x1 and x2 is supported as well adjusting to an PCIe end point with lower link configuration.

Table 7: SoC – PCI Express Gen. 4.0

Module Function	SoC PCIe Function	Lane Configuration				
		x1	x2	x4	x8	x16
COMe PCIe #16	PCIe 4.0 #0	X				
COMe PCIe #17	PCIe 4.0 #1	-	X	X		
COMe PCIe #18	PCIe 4.0 #2	-				
COMe PCIe #19	PCIe 4.0 #3	-			X	
COMe PCIe #20	PCIe 4.0 #4	X				
COMe PCIe #21	PCIe 4.0 #5	-	X	X		
COMe PCIe #22	PCIe 4.0 #6	-				
COMe PCIe #23	PCIe 4.0 #7	-				
COMe PCIe #24	PCIe 4.0 #8	X				X
COMe PCIe #25	PCIe 4.0 #9	-	X	X		
COMe PCIe #26	PCIe 4.0 #10	-				
COMe PCIe #27	PCIe 4.0 #11	-				
COMe PCIe #28	PCIe 4.0 #12	X				
COMe PCIe #29	PCIe 4.0 #13	-	X	X		
COMe PCIe #30	PCIe 4.0 #14	-				
COMe PCIe #31	PCIe 4.0 #15	-				



[1] BOM options can be offered on request to allow PCIe x1 usage for COMe Lane PCIE0-PCIE5.

3.6. HSIO Usage

The SoC PCH supports 24x HSIO lanes #0-23 (HSIO) which can be configured as PCIe Gen 3.0 lanes with up to 3 RPC, 4 RP per RPC (12 RPs max). The HSIO PCIe lanes are partly multiplexed with USB3.0 and SATA.

The HSIO lanes #0 -#15 are used as PCIe Gen 3.0 to support COMe PCIe #0 -15.

The HSIO lane #16 is used as PCIe Gen 3.0 for the onboard 1 /2.5 GbE Controller Intel i225.

The HSIO lane #18 is used as PCIe Gen 3.0 for an optional onboard NVMe SSD.

Alternatively the HSIO lanes #16, #18 and #22 can be used (by BOM option) to enable PCIe x1 lanes on COMe PCIe #0, #3 and #5.

Table 8: SoC – HSIO Usage: PCI Express Gen 3.0, SATA, USB, onboard I/O

Module Function	SoC HSIO Port	BOM Option	Lane Configuration				Comment
			x1	x2	x4	x8	
COMe PCIE #0	HSIO #0		X	X			
COMe PCIE #1	HSIO #1	HSIO #18	(X)		X		Feature on request: PCIe lane x1 ^[1]
COMe PCIE #2	HSIO #2		X	X			
COMe PCIE #3	HSIO #3	HSIO #22	(X)			X	Feature on request: PCIe lane x1 ^[1]
COMe PCIE #4	HSIO #4		X	X			
COMe PCIE #5	HSIO #5	HSIO #16	(X)		X		Feature on request: PCIe lane x1 ^[1]
COMe PCIE #6	HSIO #6		X	X			
COMe PCIE #7	HSIO #7		-				
COMe PCIE #8	HSIO #8		X	X			
COMe PCIE #9	HSIO #9		-		X		
COMe PCIE #10	HSIO #10		X	X			
COMe PCIE #11	HSIO #11		-			x	
COMe PCIE #12	HSIO #12		X	X			
COMe PCIE #13	HSIO #13		-		X		
COMe PCIE #14	HSIO #14		X	X			
COMe PCIE #15	HSIO #15		-				
Onboard GbE0 1/2.5GbE (default)	HSIO #16	No GbE0	X				
COMe SATA #1	HSIO #17						
Onboard NVMe option (default)	HSIO #18	No NVMe option	X				
COMe SATA #0	HSIO #19						
COMe USB3 #0	HSIO #20						
COMe USB3 #1	HSIO #21						
COMe USB3 #2	HSIO #23						
COMe USB3 #3	HSIO #22	No USB3 #3					



[1] BOM options can be offered on request to allow PCIe x1 usage for COMe Lane PCIE0-PCIE5.

The available PCIe bifurcation options for COMe PCIe #[0 .. 7] and COMe PCIe #[8 .. 15] are

- 1 x8
- 2 x4
- 4 x2
- Mix of x4 and x2

The following table lists the standard supported PCI Express lane configurations defined by the BIOS:

Table 9: BIOS versions

COMe Lane	Lane Configuration				
	default	var1	var2	var3	
COMe PCIe #0	x4	x4	x8	x2	
COMe PCIe #1					
COMe PCIe #2				x2	
COMe PCIe #3					
COMe PCIe #4	x4	x4		x2	
COMe PCIe #5					
COMe PCIe #6				x2	
COMe PCIe #7					
COMe PCIe #8	x8	x4	x8	x4	
COMe PCIe #9					
COMe PCIe #10					
COMe PCIe #11					
COMe PCIe #12		x4			x4
COMe PCIe #13					
COMe PCIe #14					
COMe PCIe #15					
COMe PCIe #16 - 31	x16	x16	x16	x16	

NOTICE

Please contact [JUMPTec Support](#) for other BIOS configurations.

3.7. USB

USB 3.x ports are backwards compatible with the USB 2.0 specification. The COMe-bID7 allows a maximum of four USB 3.1 Gen 1 ports including four USB 2.0 ports.

Table 10: Supported USB Features

USB 3.1 Gen 1 Ports	4x USB 3.1 Gen 1 Option: 3x USB 3.1 Gen 1 – HSIO #22 is used for COMe PCIe 3.0 lane #3 instead of USB3 #3
USB 2.0 Ports	4x USB 2.0
USB Over Current Signals	2x

See Table 8: SoC – HSIO Usage: PCI Express Gen 3.0, SATA, USB, onboard I/O.

3.8. SATA

The SATA high-speed storage interface supports two SATA Gen.3 ports with transfer rates of up to 6 Gb/s.

See Table 8: SoC – HSIO Usage: PCI Express Gen 3.0, SATA, USB, onboard I/O.

3.9. Ethernet – 1G / 2.5GBASE-T LAN

The COMe-bID7 supports one 1 GbE/2.5 GbE Base-T Ethernet interface using the Intel® i225-LM Ethernet controller for commercial temperature grades and the Intel®I225-IT for industrial temperature grades (E2).

3.10. Ethernet – 4x 10GBASE-KR

Intel® Xeon® D-1700 processor family supports up to two integrated PHY Quads with 1G/2.5G/10G/25G/40G/50G/100G rates, where with COM Express Type 7 only one PHY Quad can be used – supporting a max of 4x 10GBASE-KR ports.

Due to bandwidth limitation of the COM Express Type 7 connectors it is currently possible to use a max.of 10G rates. All interfaces of one PHY Quad must have the same configuration (same speed and same physical interface).

The COMe-bID7 can be offered in two general NIC configuration hardware options:

3.10.1. 10G LAN CEI mode (default configuration):

This mode is intended to use on modules and carriers/backplanes designed according to COM Express specification COM.0 Rev 3.1 and newer. The CEI mode defines that all external components required for a particular Ethernet mode are located outside of the COM Express module (e.g. on COM Express carrier/backplane or an expansion card), including the CEI_ID EEPROM.

3.10.2. 10G LAN Legacy mode (available on request):

For selected 10GbE modes the required external components are directly included on the COMe-bID7 module. The Legacy mode enables those components on the module, which allow to use the COMe-bID7 module on carriers/backplanes designed according to COM Express specification COM.0 Rev 3.0.

3.10.3. Overview of currently supported LAN Interfaces on COMe-bID7

3.10.3.1. 10GBASE-KR (default configuration) – CEI

Backplane Ethernet (no external PHY required)

Typical chip to chip connection e.g. via backplane or via short direct attach cable

COMe-bID7: LAN config **LEK 7.6 – 4ports**

Evaluation Platform:

COMe Evaluation Carrier T7 (68300-0000-00-0) – Note: **COMe-bID7 must be factory-preconfigured for COM.0 R3.0 regarding PCI Express support**

COMe Evaluation Carrier T7 Gen2 A2T7 (68301-0001-00-8) and expansion card ADA-COMe-T7-G2 4X 10G DAC (68301-0000-04-4)

3.10.3.2. 10G-SFI (on request) – CEI

Used for optical connection (optical SFP+ modules for multi-mode or single-mode fiber)

SFP+ direct attach (copper cable)

Extra PHY (Intel® C827/XL827) is required on carrier board

COMe-bID7: LAN config **LEK 7.0 – 4ports**

Evaluation Platform:

COMe Evaluation Carrier T7 Gen2 (68301-0001-00-8) and expansion card ADA-COMe-T7-G2 4x 10G SFP+ C827-IM1 (68301-0000-05-4)

3.10.3.3. 10G-SFI native (on request) – legacy

Used for optical connection (optical SFP+ modules for multi-mode or single-mode fiber)

SFP+ direct attach (copper cable)

COMe-bID7: LAN config **LEK 1.0 – 4ports**

Evaluation Platform:

COMe Evaluation Carrier T7 (68300-0000-00-0) - Note: **COMe-bID7 must be factory-preconfigured for COM.0 R3.0 regarding PCI Express support**

or

COMe Evaluation Carrier T7 Gen2 (68301-0001-00-8) and expansion card ADA-COMe-T7-G2 4X 10G DAC (68301-0000-04-4) – no PHY

3.10.3.4. 10GBASE-T (on request) – legacy

10 Gbps connection over twisted pair CAT6A cables with distances up to 100 meters

Typical RJ45 connection

Extra PHY (Intel® X557) is required on carrier board

COMe-bID7: LAN config **LEK 2.1 – 4ports**

Evaluation Platform:

COMe Evaluation Carrier T7 Gen2 (68301-0001-00-8) and expansion card ADA-COMe-T7-G2 4x 10G RJ45 (68301-0000-01-4).

NOTICE

Other 10G LAN configurations are available as well on request, however at this point of time w/o a corresponding evaluation platform.

Please contact [JUMPTec Support](#) for further assistance.

NOTICE

Please refer to the Application Note at the Customer Section ([Customer Section](#)).

3.11. UART

The UART serial communications interface supports up to two serial RX/TX ports supplied by the SOC. The two serial ports are defined in the COMe specification on pins A98 (SERO_TX) and A99 (SERO_RX) for UART0, and pins A101 (SER1_TX) and A102 (SER1_RX) for UART1.

3.12. Additional Features

Table 11: General, Special and Optional Features

General Features	
4x 10G Ethernet	PICMG COM.0 R3.1 compliance – CEI-interface
4x 10G Ethernet-LEK	10GBASE-KR: LEK 7.6-4ports
PCI Express COMe #16-31	PICMG COM.0 R3.1 compliance
Fast I2C	Connected to module EEPROM, carrier EEPROM and RTC clock
SPI	SPI external boot
LPC	Used for external LPC on carrier board
RTC	Supported
SM Bus	Supported
Special Features	
Embedded API	KEAPI 3 for all Supported OS KEAPI packages are included in reference image
TPM 2.0	1x TPM 2.0 (hardware)
GPIO	Start-up level configurable, GPI interrupt capable
Watchdog Support	Dual staged
Optional Features (on request)	
4x 10G Ethernet	PICMG COM.0 R3.0 compliance
4x 10G Ethernet-LEK	Configurations for: SFI native: LEK 1.0-4ports (COM.0 R3.0) 10GBASE-T: LEK 2.1-4ports (COM.0 R3.0) CEI: LEK 7.0-4ports (COM.0 R3.1)
PCI Express COMe #16-31	PICMG COM.0 R3.0 compliance
PCI Express COMe #0-7	Enable PCIe x1 lanes on COMe PCIe #1, #3, #5
NVMe SSD	Up to 1 TByte NVMe PCIe SSD NAND Flash
SODIMM sockets	4x SODIMM sockets (2x on top side + 2x on bottom side)
SODIMMs	Non-ECC SODIMMs
CPU	other CPUs than offered as standard versions
BIOS	custom BIOS configurations

3.13. Evaluation platforms for COMe-bID7 – Compatibility Matrix

Please see below the possible combinations regarding the COMe-bID7 configuration and the matching evaluation platform

COMe-bID7				Evaluation Platform		
PCIe Implementation	LAN Implementation	LAN Config and related LEK file		Carrier - PCIe Gen3 only	Adapter / Expansion	PHY
COM.0 R3.0	COM.0 R3.0 or COM.0 R3.1	4x 10GBASE-KR	7.6	COMe Eval Carrier T7 68300-0000-00-0	none	none
				COMe Eval Carrier2 T7-G2 68301-0000-00-8 (or -5)	ADA-COMe-T7-G2 4X 10G DAC - DEV-TOOL 68301-0000-04-4	none
COM.0 R3.0	COM.0 R3.0	4x 10G-SFI native	1.0	COMe Eval Carrier T7 68300-0000-00-0	none	none
				COMe Eval Carrier2 T7-G2 68301-0000-00-8 (or -5)	ADA-COMe-T7-G2 4X 10G DAC - DEV-TOOL 68301-0000-04-4	none
COM.0 R3.0	COM.0 R3.0	4x 10GBASE-T	2.1	COMe Eval Carrier2 T7-G2 68301-0000-00-8 (or -5)	ADA-COMe-T7-G2 4x 10G RJ45 - DEV-TOOL 68301-0000-01-4	PHY = 2x X557-AT2
COM.0 R3.0	COM.0 R3.1	4x 10G-SFI with PHY (CEI)	7.0	COMe Eval Carrier2 T7-G2 68301-0000-00-8 (or -5)	ADA-COMe-T7-G2 4x 10G SFP+ - C827-IM1 – DEV-TOOL 68301-0000-05-4	PHY = C827-IM1
				Carrier - PCIe Gen4 support		
COM.0 R3.1 *	COM.0 R3.0 or COM.0 R3.1 *	4x 10GBASE-KR *	7.6 *	COMe Eval Carrier2 T7-G2 68301-0001-00-8 (or -5)	ADA-COMe-T7-G2 4X 10G DAC - DEV-TOOL 68301-0000-04-4	none
COM.0 R3.1	COM.0 R3.0	4x 10G-SFI native	1.0	COMe Eval Carrier2 T7-G2 68301-0001-00-8 (or -5)	ADA-COMe-T7-G2 4X 10G DAC - DEV-TOOL 68301-0000-04-4	none
COM.0 R3.1	COM.0 R3.0	4x 10GBASE-T	2.1	COMe Eval Carrier2 T7-G2 68301-0001-00-8 (or -5)	ADA-COMe-T7-G2 4x 10G RJ45 - DEV-TOOL 68301-0000-01-4	PHY = 2x X557-AT2
COM.0 R3.1	COM.0 R3.1	4x 10G-SFI with PHY (CEI)	7.0	COMe Eval Carrier2 T7-G2 68301-0001-00-8 (or -5)	ADA-COMe-T7-G2 4x 10G SFP+ - C827-IM1 – DEV-TOOL 68301-0000-05-4	PHY = C827-IM1

* COMe-bID7 default configuration

4/ Features and Interfaces

4.1. ACPI Suspend Modes and Resume Events

The COMe-bID7 supports the S-states S0 and S5.

The following event resumes the system from S5:

- ▶ Power Button
- ▶ Wake-on-LAN

4.2. Real Time Clock (RTC)

The RTC keeps track of the current time accurately. The RTC's low power consumption enables the RTC to continue operation and keep time using a lower secondary source of power while the primary source of power is switched off or unavailable.

The COMe-bID7 supports typical RTC values of 3 V and less than 10 μ A. When powered by the mains power supply on-module regulators generate the RTC voltage, to reduce RTC current draw. The RTC's battery voltage range is 2.8 V to 3.47 V.



It is not recommended to run a system without a RTC battery on the carrier board. Even if the RTC battery is not required to keep the actual time and date when main power is off, a missing RTC battery will cause other side effects such as longer boot times. Intel processor environments are generally designed to rely on RTC battery voltage.

4.3. NVMe Storage (Option)

The NVMe SSD Flash memory supports up to one TByte. The optional NVMe SSD uses HSIO #18 of the SoC.

4.4. Hardware Monitor (HWM)

The Hardware Monitor (HWM) controls the health of the system by monitoring critical aspects such as temperatures, power supply voltages and fan speed for cooling. The temperature is controlled by temperature sensors supported via the SMBus interface and directly from the CPU using Intel's® Platform Environment Control Interface (PECI) 3.0 interface. The SMART FAN™ technology controls the duty cycle of the fan output with temperature setting points. This enables flexible fan control for cooling solutions and noise sensitive solutions. For system protection, users can set threshold values for alarm signals.

4.5. Trusted Platform Module (TPM)

A Trusted Platform Module (TPM) stores RSA encryption keys specific to the host system for hardware authentication. The term TPM refers to the set of specifications applicable to TPM chips. The SPI bus connects the TPM chip to the CPU.

Each TPM chip contains an RSA key pair called the Endorsement Key (EK). The pair is maintained inside the chip and cannot be accessed by software. The Storage Root Key (SRK) is created when a user or administrator takes ownership of the system. The TPM generates the key pair based on the Endorsement Key and an owner-specified password.

A second key, called an Attestation Identity Key (AIK) protects the device against unauthorized firmware and software modification by hashing critical sections of firmware and software before they are executed. When the system attempts to connect to the network, the hashes are sent to a server that verifies that they match the

expected values. If any of the hashed components have been modified since the last start, the match fails, and the system cannot gain entry to the network.

4.6. Onboard Fan Connector

The analog output voltage on this connector is generated via a discrete linear voltage regulator from the PWM signal of the HWM. It is clipped at 12 V (+/- 10 %) across the whole input range of the module to prevent fan damage at higher voltages.

The maximum supply current to the fan connected to the on-module fan connector is 350 mA if the input voltage is below 13.0 V and is further limited to 150 mA if the input voltage to the module is between 13.0 V and 20.0 V.

Table 12: Onboard Fan Connector

Pin	Signal	Description	Type
1	Fan_Tach_IN#	Fan Input voltage from COMe connector	Input
2	V_FAN	12 V ±10% (max.) across module input range	PWR
3	GND	Power GND	PWR

NOTICE

Always check the fan specification according to the limitations of the supply current and supply voltage.

4.7. Watchdog Timer (WDT) Dual Stage

The watchdog timer interrupt is a hardware or software timer implemented by the module to the carrier board if there is a fault condition in the main program; the watchdog triggers a system reset or other corrective actions after a specific time, with the aim to bring the system back from a non-responsive to normal state.

The COMe-bID7 supports an independently programmable watchdog that works with two stages that can be used stage by stage.

Table 13: Dual Staged Watchdog Timer- Time-Out Events

0000b	No action	Stage is off and will be skipped
0001b	Reset	Restarts the module and starts a new POST and operating system
0101b	Delay -> No action	Might be necessary when an operating system must be started and the time for the first trigger pulse must be extended. Only available in the first stage!
1000b	WDT Only	Triggers WDT pin on the carrier board connector (COM Express® pin B27) only
1001b	Reset + WDT	
1101b	DELAY + WDT -> No action	

4.8. Watchdog Timer Signal

The watchdog interrupt (WDT) on COM Express® pin B27 on COM Express® connector indicates a Watchdog time-out event has not been triggered within a set time. The WDT signal is configurable to any of the two stages. After reset, the signal is automatically de-asserted. If de-assertion is necessary during runtime, contact JUMPttec Support for further help.

4.9. Hyper-Threading

Hyper-Threading (officially termed Hyper Threading Technology or HTT) is an Intel®-proprietary technology used to improve parallelization of computations performed on PCs. Hyper-Threading works by duplicating certain sections of the processor – those that store the architectural state but not duplicating the main execution resources. This allows a Hyper-Threading equipped processor to pretend to be two “logical” processors to the host operating system, allowing the operating system to schedule two threads or processes simultaneously. Hyper-Threading Technology always depends on the Operating System.

4.10. Fast I2C

The internal I2C bus transfers data between components on the same module and the external I2C bus transfers data

between I2C devices connected on the bus. The Fast I2C bus transfers data with rates up to 400 kHz.

To change the I2C bus speed, in the BIOS setup menu select:

Advanced>Miscellaneous>I2C Speed> 400 kHz to 1 kHz

The default speed is 200 kHz.

The following table specifies the devices connected the accessible I2C bus including the I2C address. The I2C bus is available at the COM Express® connector pin B33, I2C_CK and pin B34, I2C_DAT.

Table 14: I2C Bus Port Address

8-bit Address	7-bit Address	Used For	Available
A0h	50h	Module embedded EEPROM (Eeep)	Yes
A Eh	57h	Carrier board EEPROM	Optional

4.11. LPC

The Low Pin Count (LPC) interface is pin shared with eSPI, where the LPC interface is the default connection from the embedded controller to the COMe connector.

The Low Pin Count (LPC) Interface signals are connected to the LPC Bus located in the Soc. The LPC low speed interface can be used for peripheral circuits such as an external Super I/O Controller that typically combines legacy-device support into a single IC. The implementation of this subsystem complies with the COM Express® specification. The COM Express® Design Guide maintained by PICMG provides implementation information or refer to the official PICMG documentation for more information. The LPC bus does not support DMA (Direct Memory Access). When more than one device is used on LPC, a zero delay clock buffer is required. This leads to limitations for ISA bus and SIO (standard I/O(s) like floppy or LPT interfaces) implementation. The COMe-bID7 LPC clock buffer allows for the connection of three LPC devices

4.12. Serial Peripheral Interface (SPI)

The Serial Peripheral Interface (SPI) bus is a synchronous serial data link where devices communicate in master/slave mode and the master device initiates the data frame. Multiple slave devices are allowed with individual slave select (chip select) lines.

4.12.1. SPI Boot

The COMe-bID7 supports on-module and on-carrier boot from an SPI Flash.

The pins A34 (BIOS_DIS0#) and B88 (BIOS_DIS1#) configure the SPI Flash to be used, see Table 15.

Table 15: SPI Boot Pin Configuration

BIOS_DIS0#	BIOS_DIS1#	Boot Bus	Function
Open	Open	SPI	Boot on-module SPI
Open	GND	SPI	Boot on-carrier SPI

Table 16: Supported SPI Boot Flash

Size	Manufacturer	Part Number	Package Type	Manufact. ID
32 MByte	Winbond	W25Q256JVEIQ	WS0N-8 8x6 mm	EFh

4.12.2. SPI Flash Update

1. On-board SPI Flash

Initially, the EFI Shell is booted with an USB key containing the binary used to flash the on-module SPI Flash chip.

The command line is:

```
AfuEfix64\EtaAfuOemEfi64.efi BID7Rxxx.bin /p /b /n /k /me /x
```



It intentionally does not flash the 10GbE region to avoid destroying 10GbE MAC addresses when only Bios update is required.

See further information in the BIOS package itself available on the [Customer Section](#).

2. External SPI Flash

To program the external SPI Flash on the carrier board with the BIOS binary, use an external programmer.

When booting from the external SPI Flash on the carrier board if the COM Express® module is exchanged for another module of the same type, the Intel® Management Engine (ME) will fail during the next start. The Management Engine (ME) binds itself to every module it has previously flashed which in the case of an external SPI Flash is the module present when flashed.



To avoid this issue, after changing the COM Express® module for another module, conduct a complete flash from the external SPI Flash device. If disconnecting and reconnecting the same module again, this step is not necessary.



Register for the [Customer Section](#) to get access to BIOS downloads and PCN service.

4.13. System Management Bus (SMB)

The System Management Bus (SMB) is a simple 2-wire bus for low-speed system management communication. The PCH controls the SMB. The module's SMB, routed to the COMe connector connects to the hardware controller and the optional NVMe.

The 8-bit SMBus address uses the LSB (bit 0) for the direction of the device.

- ▶ Bit0 = 0 defines the write address

- ▶ Bit0 = 1 defines the read address

The following table specifies the 8-bit and 7-bit SMBus write address for all devices.

Table 17: SMBus Address

8-bit Address	7-bit Address	Device	Description
0x10	0x08	SoC - reserved	
0x5C	0x2E	Hardware Monitor NCT7802Y	Do not use this address for external devices under any circumstances
0x88	0x44	SoC - reserved	
0xD4	0x6A	PCIe Clock Buffer	

4.14. GPIO

The eight GPIO pins support four inputs pins (A54 for GPIO, A63 for GPI1, A67 for GPI2 and A85 for GPI3) and four output pins (A93 for GPO0, B54 for GPO1, B57 for GPO2 and B63 for GPO3) by default. The four GPI[0-3] pins are pulled high with a pull-up resistor (e.g. 100 K ohms) and the four GPO[0-3] pins are pulled low with a pull-down resistor (e.g. 100 K ohms) on the module.

To change the default GPIO signal-state users are required to make BIOS and/or OS-driver changes, and additional hardware changes by adding external termination resistors on the carrier board to override the weak on-module pull-up resistors with a lower resistance pull-down (e.g. 10 K ohms), or pull-down resistors with a lower resistance pull-up (e.g. 10 K ohms).

4.15. NS-CI

The COMe-bID7 supports the NC-SI (Network Controller Sideband Interface) physical interface. The NC-SI signals from the D-1700 SOC are routed to the COMe connector.

5/ Accessories

5.1. Product Specific Accessories

Table 18: Product Specific Accessories List

Product Number	Carrier	Description
Standard		
68300-0000-00-0	COMe Eval Carrier T7	COM Express® Eval Carrier Type 7
68301-0001-00-8	COMe Eval Carrier T7 G2-8 R3.1	COM Express® Eval Carrier Type 7 Gen2, 8 mm stack-up, according COM.0 Rev 3.1
68301-0000-00-8	COMe Eval Carrier T7 G2-8 R3.0	COM Express® Eval Carrier Type 7 Gen2, 8 mm stack-up, according COM.0 Rev 3.0
Available on request		
68301-0001-00-5	COMe Eval Carrier T7 G2-5 R3.1	COM Express® Eval Carrier Type 7 Gen2, 5 mm stack-up, according COM.0 Rev 3.1
68301-0000-00-5	COMe Eval Carrier T7 G2-5 R3.0	COM Express® Eval Carrier Type 7 Gen2, 5 mm stack-up, according COM.0 Rev 3.0

Product Number	AdapterCards to be used with COMe Eval Carrier T7 G2	Description
68301-0000-01-4	ADA-COMe-T7-G2 4x 10G RJ45 - DEV-TOOL	4x RJ45: 10GBASE-KR-to-10GBASE-T via 2x Intel PHY X557-AT2
68301-0000-04-4	ADA-COMe-T7-G2 4X10G DAC - DEV-TOOL	4x DAC: 10GBASE-KR signals directly routed from COMe connector to SFP+ cages
68301-0000-05-4	ADA-COMe-T7-G2 4x10G SFP+ - C827-IM1 – DEV-TOOL	4x SFP+: 10GBASE-KR-to-SFI via Intel PHY C827-IM1

Table 19: Cooler and Heatspreader

Product Number	Product	Description
68009-0000-99-0	HSP COMe-bID7 (E2) threaded mounting holes	Heatspreader for COMe-bID7 (E2), with Cu-core, threaded mounting holes
68009-0000-99-1	HSP COMe-bID7 (E2) through holes	Heatspreader for COMe-bID7 (E2), with Cu-core, through holes
38025-0000-99-0C05	HSK COMe-basic active (w/o HSP)	Active Cooler for COMe-bID7 to be mounted on HSP
38025-0000-99-0C06	HSK COMe-basic passive (w/o HSP)	Passive Cooler for COMe-bID7 to be mounted on HSP

5.2. General Accessories

Table 20: General Accessories List

Product Number	Mounting	Description
38017-0000-00-5	COMe Mount KIT 5mm 1set	Mounting Kit for 1 module including screws for 5mm connectors
38017-0000-00-0	COMe Mount KIT 8mm 1set	Mounting Kit for 1 module including screws for 8mm connectors
Product Number	Cables	Description
96079-0000-00-0	KAB-HSP 200mm	Cable adapter to connect Fan to module (COMe basic/compact)
96079-0000-00-2	KAB-HSP 40mm	Cable adapter to connect Fan to module (COMe basic/compact)

Table 21: Memory Modules

Part Number	Memory (ECC)	Description
97030-0832-BID7	DDR4-3200 SODIMM 8 GB_BID7	DDR4-3200, 8 GB, 260P, 1600 MHz, PC4-3200 SODIMM, ECC
97030-1632-BID7	DDR4-3200 SODIMM 16 GB_BID7	DDR4-3200, 16 GB, 260P, 1600 MHz, PC4-3200 SODIMM, ECC
97030-3232-BID7	DDR4-3200 SODIMM 32 GB_BID7	DDR4-3200, 32 GB, 260P, 1600 MHz, PC4-3200 SODIMM ECC
97031-0832-BID7	DDR4-3200 SODIMM 8 GB E2_BID7	DDR4-3200, 8 GB, 260P, 1600 MHz, PC4-3200 SODIMM, ECC, industrial temperature
97031-1632-BID7	DDR4-3200 SODIMM 16 GB E2_BID7	DDR4-3200, 16 GB, 260P, 1600 MHz, PC4-3200 SODIMM, ECC, industrial temperature
97031-3232-BID7	DDR4-3200 SODIMM 32 GB E2_BID7	DDR4-3200, 32 GB, 260P, 1600 MHz, PC4-3200 SODIMM, ECC, industrial temperature



Non-ECC SODIMMs are available on request.

6/ Electrical Specification

6.1. Supply Voltage

Table 22 provides information regarding the supply voltage specified at the COM Express® connector.

Table 22: COM Express® Connector Electrical Specifications

	Commercial Grade	Industrial Grade
VCC	8.5 V – 20 V	12 V DC +/- 5%
Standby	5V DC +/- 5% (5 VSB is not mandatory for operation)	5 V DC +/- 5%
RTC	2.8 V - 3.47 V	2.8 V - 3.47 V



5 V Standby voltage is not mandatory for operation.

6.2. Power Supply Rise Time

The input voltages should rise from $\leq 10\%$ of nominal to within the regulation ranges within 0.1 ms to 20 ms.

There must be a smooth and continuous ramp of each DC input voltage from 10% to 90% of its final set-point following the ATX specification.

6.3. Supply Voltage Ripple

Maximum 100 mV peak to peak 0 – 20 MHz.

6.4. Power Consumption

The COMe-bID7 supports D-1700 / D-1800 processor SKUs up to 90 W TDP.



For Information on Detailed Power Consumption measurements in all states and benchmarks for CPU, Graphics and Memory performance, refer to the Application Note at the [Customer Section](#).

6.5. ATX Mode

By connecting an ATX power supply with VCC and 5VSB, PWR_OK is set to low level and VCC is off. Press the Power Button to enable the ATX PSU setting PWR_OK to high level and powering on VCC. The ATX PSU is controlled by the PS_ON# signal which is generated by SUS_S3# through inversion.

In ATX Mode VCC can be 8.5 V – 20 V for commercial grade modules and 12 V DC +/- 5% for industrial grade modules.

Table 23: ATX Mode

State	PWRBTN#	PWR_OK	V5_StdBy	PS_ON#	VCC
G3	x	x	0V	x	0V
S5	high	low	5V	high	0V
S5 → S0	PWRBTN Event	low → high	5V	high → low	0 V → VCC
S0	high	high	5V	low	VCC

6.6. Single Supply Mode

In single supply mode, without 5V standby the module will start automatically when VCC power is connected and Power Good input is open or at high level (internal PU to 3.3V).

VCC can be 8.5 V – 20 V for commercial grade modules and 12 V DC +/- 5% for industrial grade modules.

To power on the module from S5 state press the power button or reconnect VCC. Suspend/Standby States are not supported in Single Supply Mode.

Table 24: Single Supply Mode

State	PWRBTN#	PWR_OK	V5_StdBy	VCC
G3	0	0	0	0
G3 → S0	high	open / high	OPEN	connecting VCC
S5	high	open / high	OPEN	VCC
S5 → S0	PWRBTN Event	open / high	OPEN	reconnect VCC



All ground pins have to be tied to the ground plane of the carrier board.

NOTICE

If any of the supply voltages drops below the allowed operating level longer than the specified hold-up time, all the supply voltages should be shut down and left OFF for a time long enough to allow the internal board voltages to discharge sufficiently. If the OFF time is not observed, parts of the board or attached peripherals may work incorrectly or even suffer a reduction of MTBF.

The minimum OFF time depends on the implemented PSU model and other electrical factors and needs to be measured individually for each case.

7/ Power Control

7.1. Power Supply

The COMe-bID7 supports a power input from 8.5 V to 20 V in the commercial grade version, but 12 V DC +/- 5% in the industrial version. The supply voltage is applied through the VCC pins (VCC) of the module connector.

Optionally 5 V +/- 5% can be applied to the V_5V_STBY pins and allows support for wake-up suspend-to-disk and soft-off state when the VCC power is removed.



Suspend-to-RAM (S3) and Hibernate (S4) is not supported by the Xeon D-1700 product family.

7.2. Power Supply Control Settings

The power supply control settings are set in the BIOS and enable the module to shut down, rest and wake from standby properly.

Table 25: Power Supply Control Settings

Power Button (PWRBTN#)	Pin B12	To start the module using the power button, the PWRBTN# signal must be at least 50 ms ($50\text{ ms} \leq t < 4\text{ s}$, typical 400 ms) at low level (Power Button Event). Pressing the power button for at least four seconds turns off power to the module (Power Button Override).
Power Good (PWR_OK)	Pin B24	PWR_OK is internally pulled up to 3.3 V and must be at the high level to power on the module. This can be driven low to hold the module from powering up as long as needed. The carrier needs to release the signal when ready. Low level prevents the module from entering the S0 state (Wake up event). A falling edge during S0 (Wake up event) causes a direct switch to S5 (Power Failure).
Reset Button (SYS_RESET#)	Pin B49	When the SYS_RESET# pin is detected active (falling edge triggered), it allows the processor to perform a “graceful” reset, by waiting up to 25 ms for the SMBus to go idle before forcing a reset, even though activity is still occurring. Once the reset is asserted, it remains asserted for 5 ms to 6 ms regardless of whether the SYS_RESET# input remains asserted or not.
SM-Bus Alert (SMB_ALERT#)	Pin B15	With an external battery manager present and SMB_ALERT# connected, the module always powers on even if the BIOS switch “After Power Fail” is set to “Stay Off”.
Battery low (BATLOW#)	Pin A27	BATLOW# can be used as a power fail indication a Type 7 system where assertion prevents wake from S3-S5 states.

8/ Standards and Certification

The COMe-bID7 complies with the listed European Council directives or the latest status thereof:

- ▶ European Council directive relating to Electromagnetic Compatibility (2014/30/EU)
- ▶ General Product safety Directive (2001/95/EC)
- ▶ Low Voltage directive (2014/35/EU)

The following table provides information regarding standards that are elements of the CE declaration and additional standard compliancy information. For more information, contact the [JUMPtec Support](#).

Table 26: Standards and Certification Compliance

Standard		Definition
EMC	Emission	EN 55032:2015 + A11:2020 Electromagnetic compatibility of multimedia equipment - Emission Requirements
	Immunity	EN IEC 61000-6-2:2019 Electromagnetic compatibility (EMC) – Part 6-2: Generic standards – Immunity standard for industrial environment
CE		<p>Complies with the European Council Directive on the approximation of the laws of the member states relating to Electromagnetic Compatibility 2014/30/EU, General Product Safety Directive 2001/95/EC, Low Voltage Directive 2014/35/EU and Restriction of Hazardous Substances in Electrical and Electronic Equipment, RoHS Directive 2011/65/EU + 2015/863/EU + 2017/2102/EU or the latest status thereof.</p> <p>EN 62368-1:2014/AC:2015: Audio/video , information and communication technology equipment Part 1: Safety requirements</p> <p>EN IEC 62368-1:2020/A11:2020: Audio/video, information and communication technology equipment Part 1: Safety requirements</p> <p>EN 55032:2015/A11:2020: Electromagnetic compatibility (EMC) of multimedia equipment Emission Requirements</p> <p>EN 61000-6-2:2005 +Cor.:2005: Electromagnetic compatibility (EMC) - Part 6-2: Generic standards Immunity for industrial environments+ CENELEC Cor.:2005</p> <p>EN IEC 61000-6-2 :2019: Electromagnetic compatibility (EMC) - Part 6-2: Generic standards Immunity for industrial environments</p>
UK Declaration of Conformity		<p>BS EN 62368-1:2014/AC:2015: Audio/video, information and communication technology equipment Part 1: Safety requirements</p> <p>BS EN IEC 62368-1:2020/A11:2020: Audio/video, information and communication technology equipment Part 1: Safety requirements (IEC 62368-1:2018)</p> <p>BS EN 55032:2015/A11:2020: Electromagnetic compatibility of multimedia equipment - Emission Requirements</p> <p>BS EN 61000-6-2:2005/AC:2005: Electromagnetic compatibility (EMC) - Part 6-2: Generic standards - Immunity for industrial environments+CENELEC-Cor.:2005</p> <p>BS EN IEC 61000-6-2:2019: Electromagnetic compatibility (EMC). Part 6-2:Generic Standards - Immunity for industrial environments</p>
UL		CSA C22.2 NO. 62368-1, 3rd Ed.
Shock		DIN EN 60068-2-27: February 2010 Non-operating shock – (half-sinusoidal, 11 ms, 15 g)
Vibration		DIN EN 60068-2-6: October 2008 Non-operating vibration – (sinusoidal, 10 Hz – 2000 Hz, +/- 0.15 mm, 2 g)
RoHS		Directive 2011/65/EU Restriction of Hazardous substance in electrical and Electronic Equipment (RoHS)
WEEE		Directive 2012/19/EU Waste Electrical and Electronic Equipment (WEEE)
REACH		Regulation (EC) No. 1907/2006 Registration, Evaluation, Authorization and Restriction of Chemicals (REACH)

8.1. MTBF

The MTBF (Mean Time Before Failure) value was calculated using a combination of the manufacturer’s test data, (if available) and the Telcordia (Bellcore) issue 2, calculation for the remaining parts.


The Telcordia calculation used is “Method 1 Case 3” in a ground benign, controlled environment. This particular method takes into account varying temperature and stress data and the system is assumed to have not been burned-in. Other environmental stresses (such as extreme altitude, vibration, salt-water exposure) lower the MTBF value.



The MTBF estimated value above assumes no fan, but a passive heat sinking arrangement. Estimated RTC battery life (as opposed to battery failures) is not accounted for and needs to be considered separately. Battery life depends on both temperature and operating conditions. When the module is connected to external power, the only battery drain is from leakage paths.

Figure 4 shows the MTBF de-rating value for the module variant when used in an office or telecommunications environment.

Figure 4: MTBF De-rating Values (Reliability report: COMe-bID7 E2 D-1747NTE EV)




9/ Mechanical Specification

9.1. Dimensions

The dimensions of the module are 95.0 mm x 125.0 mm.

Figure 5: Module Dimensions




CAD drawings are available at the [Customer Section](#).

9.1.1. Height

The height of the module depends on the height of the implemented cooling solution. The height of the cooling solution is not specified in the COM Express® specification.

The COM Express® specification defines a module height of approximately 13 mm from module PCB bottom to heatspreader top, as shown in Figure 6: Module Height below.

Figure 6: Module Height



9.1.2. Module Height with Four SODIMM Memory Sockets

The overall height of the module and carrier board depends on whether the COMe-bID7 is implemented with:

- ▶ two SODIMMs both located on module's top side (standard variant)
- ▶ four SODIMMs with two located on module's top side and bottom side


The COMe-bID7 variant with four SODIMM memory is outside the basis COM Express® PICMG COM.0 Rev 3.0 Type 7 module form factor and requires the carrier board to be designed to support an 8 mm high COMe connector. To calculate the total height of the module and carrier take both the top side height and the bottom side height into consideration.



The 4x SODIMM variant has SODIMM sockets assembled on the bottom side of the module and requires a carrier board with 8 mm high COMe connectors and a component free area on the carrier board below the module SODIMM sockets.

The following figure shows the module board with the optional variant SODIMMs assembled on the top side and the bottom side of the board.

Figure 7: Module Top and Bottom SODIMM Assembly (Option)



9.2. Thermal Management, Heatspreader and Cooling Solutions

A heatspreader plate assembly is available from JUMPtec for the COMe-bID7. The heatspreader plate on top of this assembly is NOT a heat sink. It works as a COM Express®-standard thermal interface to use with a heat sink or external cooling devices.

External cooling must be provided to maintain the heatspreader plate at proper operating temperatures. Under worst case conditions, the cooling mechanism must maintain an ambient air and heatspreader plate temperature on any spot of the heatspreader's surface according the module specifications:

60°C for commercial grade modules

85°C for industrial temperature grade modules (E2/XT)

You can use many thermal-management solutions with the heatspreader plates, including active and passive approaches.

The optimum cooling solution varies, depending on the COM Express® application and environmental conditions. Active or passive cooling solutions provided from JUMPtec for the COMe-bID7 are usually designed to cover the power and thermal dissipation for a commercial grade temperature range used in a housing with proper air flow.



HOT Surface!

Do NOT touch! Allow to cool before servicing.

9.2.1. Heatspreader Dimensions

The COMe-bID7 heatspreaders are built from aluminum with a copper core. The heatspreaders have threads or through holes for mounting and are black anodized. The devices are delivered single packed.


NOTICE

The heatspreaders 68009-0000-99-0 and 68009-0000-99-1 can be used with JUMPtec's active and passive cooling solutions 38025-0000-99-0C05 and 38025-0000-99-0C06.

9.2.1.1. Heatspreader 68009-0000-99-0 with Threads

Figure 8: Heatspreader 68009-0000-99-0 Dimensions


*All dimensions shown in mm.



9.2.1.2. Heatspreader 68009-0000-99-1 with Through Holes


Figure 9: Heatspreader 68009-0000-99-1 Dimensions

*All dimensions shown in mm.




10/ COMe Connector Pin-out List

Figure 10: COMe Connector with 220 pins



This table lists the pins and signals according to the PICMG specification COM.0 Rev 3.1 and Rev 3.0 Type 7 standard.

Figure 11: COMe Connector Pinout



NOTICE

To protect external power lines of peripheral devices, make sure that: the wires have the right diameter to withstand the maximum available current the enclosure of the peripheral device fulfills the fire-protection requirements of IEC/EN62368

Table 27: Pin-out List A

Grey background for pins different between COM.0 R.0 and R3.1

Pin	Signal	Description	Type	Termination / Comment
A1	GND	Power Ground	PWR GND	-
A2	GBE0_MDI3-	Ethernet Media Dependent Interface 3 -	DP-I/O	-
A3	GBE0_MDI3+	Ethernet Media Dependent Interface 3 +	DP-I/O	-
A4	R3.0: GBE0_LINK100# R3.1: GBE0_LINK_MID#	Ethernet Speed LED	OD	-
A5	R3.0: GBE0_LINK1000# R3.1: GBE0_LINK_MAX#	Ethernet Speed LED	OD	-
A6	GBE0_MDI2-	Ethernet Media Dependent Interface 2 -	DP-I/O	-
A7	GBE0_MDI2+	Ethernet Media Dependent Interface 2 +	DP-I/O	-
A8	GBE0_LINK#	LAN Link LED	OD	-
A9	GBE0_MDI1-	Ethernet Media Dependent Interface 1 -	DP-I/O	-
A10	GBE0_MDI1+	Ethernet Media Dependent Interface 1 +	DP-I/O	-
A11	GND	Power Ground	PWR GND	-
A12	GBE0_MDI0-	Ethernet Media Dependent Interface 0 -	DP-I/O	-
A13	GBE0_MDI0+	Ethernet Media Dependent Interface 0 +	DP-I/O	-
A14	GBE0_CTREF	Center Tab Reference Voltage	REF	1uF capacitor to GND
A15	SUS_S3#	Suspend To RAM (or deeper) Indicator	O-3.3	-
A16	SATA0_TX+	SATA Transmit Pair 0 +	DP-O	AC Coupled on Module
A17	SATA0_TX-	SATA Transmit Pair 0 -	DP-O	AC Coupled on Module
A18	SUS_S4#	Suspend To Disk (or deeper) Indicator	O-3.3	-
A19	SATA0_RX+	SATA Receive Pair 0 +	DP-I	AC Coupled on Module
A20	SATA0_RX-	SATA Receive Pair 0 -	DP-I	AC Coupled on Module
A21	GND	Power Ground	PWR GND	-
A22	PCIE_TX15+	PCI Express Lane 15 Transmit +	DP-O	AC Coupled on Module

Pin	Signal	Description	Type	Termination / Comment
A23	PCIE_TX15-	PCI Express Lane 15 Transmit -	DP-O	AC Coupled on Module
A24	SUS_S5#	Soft Off Indicator	O-3.3	-
A25	PCIE_TX14+	PCI Express Lane 14 Transmit +	DP-O	AC Coupled on Module
A26	PCIE_TX14-	PCI Express Lane 14 Transmit -	DP-O	AC Coupled on Module
A27	BATLOW#	Battery Low	I-3.3	PU 10k 3.3V (S5)
A28	SATA_ACT#	Serial ATA activity LED	O-3.3	PU 10k 3.3V (S0)
A29	RSVD	Reserved for future use	NC	-
A30	RSVD	Reserved for future use	NC	-
A31	GND	Power Ground	PWR GND	-
A32	RSVD	Reserved for future use	NC	-
A33	RSVD	Reserved for future use	NC	-
A34	BIOS_DIS0#/ESPI_SAF S	BIOS Selection Strap 0	I-3.3	PU 10k 3.3V (S5)
A35	THRMTRIP#	Thermal Trip	O-3.3	-
A36	PCIE_TX13+	PCI Express Lane 13 Transmit +	DP-O	AC Coupled on Module
A37	PCIE_TX13-	PCI Express Lane 13 Transmit -	DP-O	AC Coupled on Module
A38	GND	Power Ground	PWR GND	-
A39	PCIE_TX12+	PCI Express Lane 12 Transmit +	DP-O	AC Coupled on Module
A40	PCIE_TX12-	PCI Express Lane 12 Transmit -	DP-O	AC Coupled on Module
A41	GND	Power Ground	PWR GND	-
A42	USB2-	USB 2.0 Data Pair Port 2 -	DP-I/O	-
A43	USB2+	USB 2.0 Data Pair Port 2 +	DP-I/O	-
A44	USB_2_3_OC#	USB Overcurrent Indicator Port 2/3	I-3.3	PU 10k 3.3V (S5); Connected via OR to USB_0_1_OC#
A45	USB0-	USB 2.0 Data Pair Port 0 -	DP-I/O	-
A46	USB0+	USB 2.0 Data Pair Port 0 +	DP-I/O	-
A47	VCC_RTC	Real-Time Clock Circuit Power Input	PWR 3V	Voltage range 2.0V to 3.3V (3.0V Nominal)
A48	RSVD	Reserved for future use	NC	-
A49	GBE0_SDP	Gigabit Eth. Controller 0 SW-Definable Pin	I/O-3.3 (S5)	-
A50	LPC_SERIRQ/ESPI_CS1 #	Serial Interrupt Request	I/OD-3.3	PU 8k2 3.3V (S0)
A51	GND	Power Ground	PWR GND	-
A52	PCIE_TX5+	PCI Express Lane 5 Transmit +	DP-O	AC Coupled on Module
A53	PCIE_TX5-	PCI Express Lane 5 Transmit -	DP-O	AC Coupled on Module
A54	GPIO	General Purpose Input 0	I-3.3	PU 100k 3.3V (S0)
A55	PCIE_TX4+	PCI Express Lane 4 Transmit +	DP-O	AC Coupled on Module
A56	PCIE_TX4-	PCI Express Lane 4 Transmit -	DP-O	AC Coupled on Module

Pin	Signal	Description	Type	Termination / Comment
A57	GND	Power Ground	PWR GND	-
A58	PCIE_TX3+	PCI Express Lane 3 Transmit +	DP-O	AC Coupled on Module
A59	PCIE_TX3-	PCI Express Lane 3 Transmit -	DP-O	AC Coupled on Module
A60	GND	Power Ground	PWR GND	-
A61	PCIE_TX2+	PCI Express Lane 2 Transmit +	DP-O	AC Coupled on Module
A62	PCIE_TX2-	PCI Express Lane 2 Transmit -	DP-O	AC Coupled on Module
A63	GPI1	General Purpose Input 1	I-3.3	PU 100k 3.3V (S0)
A64	PCIE_TX1+	PCI Express Lane 1 Transmit +	DP-O	AC Coupled on Module
A65	PCIE_TX1-	PCI Express Lane 1 Transmit -	DP-O	AC Coupled on Module
A66	GND	Power Ground	PWR GND	-
A67	GPI2	General Purpose Input 2	I-3.3	PU 100k 3.3V (S0)
A68	PCIE_TX0+	PCI Express Lane 0 Transmit +	DP-O	AC Coupled on Module
A69	PCIE_TX0-	PCI Express Lane 0 Transmit -	DP-O	AC Coupled on Module
A70	GND	Power Ground	PWR GND	-
A71	PCIE_TX8+	PCI Express Lane 8 Transmit +	DP-O	AC Coupled on Module
A72	PCIE_TX8-	PCI Express Lane 8 Transmit -	DP-O	AC Coupled on Module
A73	GND	Power Ground	PWR GND	-
A74	PCIE_TX9+	PCI Express Lane 9 Transmit +	DP-O	AC Coupled on Module
A75	PCIE_TX9-	PCI Express Lane 9 Transmit -	DP-O	AC Coupled on Module
A76	GND	Power Ground	PWR GND	-
A77	PCIE_TX10+	PCI Express Lane 10 Transmit +	DP-O	AC Coupled on Module
A78	PCIE_TX10-	PCI Express Lane 10 Transmit -	DP-O	AC Coupled on Module
A79	GND	Power Ground	PWR GND	-
A80	GND	Power Ground	PWR GND	-
A81	PCIE_TX11+	PCI Express Lane 11 Transmit +	DP-O	AC Coupled on Module
A82	PCIE_TX11-	PCI Express Lane 11 Transmit -	DP-O	AC Coupled on Module
A83	GND	Power Ground	PWR GND	-
A84	NCSI_TX_EN	NC-SI Transmit enable	I-3.3 (S5)	PD 10k
A85	GPI3	General Purpose Input 3	I-3.3	PU 100k 3.3V (S0)
A86	SPI_TPM_CS2_EXT#	SPI CS2 External Option	O-3.3/NC	Series 0R DNI
A87	RSVD	Reserved for future use	NC	-
A88	PCIE_CK_REF+	Reference PCI Express Clock +	DP-O	100MHz
A89	PCIE_CK_REF-	Reference PCI Express Clock -	DP-O	100MHz
A90	GND	Power Ground	PWR GND	-
A91	SPI_POWER	3.3V Power Output Pin for ext. SPI flash	O-3.3	100mA (max.)

Pin	Signal	Description	Type	Termination / Comment
A92	SPI_MISO	SPI Master IN Slave OUT	I-3.3	
A93	GPO0	General Purpose Output 0	O-3.3	PD 100k
A94	SPI_CLK	SPI Clock	O-3.3	
A95	SPI_MOSI	SPI Master Out Slave In	O-3.3	
A96	TPM_PP	TPM Physical Presence	I-3.3	PD 10k
A97	TYPE10#	Indicates TYPE10# to carrier board	NC	-
A98	SERO_TX	Serial Port 0 TXD	O-3.3	20V protection circuit implemented on module, PD on carrier needed for proper operation
A99	SERO_RX	Serial Port 0 RXD	I-5T	PU 10k 3.3V (S0); 20V protection circuit implemented on module
A100	GND	Power Ground	PWR GND	-
A101	SER1_TX	Serial Port 1 TXD	O-3.3	20V protection circuit implemented on module, PD on carrier needed for proper operation
A102	SER1_RX	Serial Port 1 RXD	I-5T	PU 10k 3.3V (S0); 20V protection circuit implemented on module
A103	LID#	LID Switch Input	I-3.3	PU 47k 3.3V (S5); 20V protection circuit implemented on module
A104	VCC_12V	Main Input Voltage	PWR	-
A105	VCC_12V	Main Input Voltage	PWR	-
A106	VCC_12V	Main Input Voltage	PWR	-
A107	VCC_12V	Main Input Voltage	PWR	-
A108	VCC_12V	Main Input Voltage	PWR	-
A109	VCC_12V	Main Input Voltage	PWR	-
A110	GND	Power Ground	PWR GND	-

Table 28: Pin-out List B

Pin	Signal	Description	Type	Termination / Comment
B1	GND	Power Ground	PWR GND	-
B2	GBE0_ACT#	Ethernet Activity LED	OD	-
B3	LPC_FRAME#/ESPI_CS0#	LPC Frame Indicator	O-3.3	-
B4	LPC_AD0/ESPI_IO_0	LPC Multiplexed Command, Addr & Data 0	I/O-3.3	-
B5	LPC_AD1/ESPI_IO_1	LPC Multiplexed Command, Addr & Data 1	I/O-3.3	-

Pin	Signal	Description	Type	Termination / Comment
B6	LPC_AD2/ESPI_IO_2	LPC Multiplexed Command, Addr & Data 2	I/O-3.3	-
B7	LPC_AD3/ESPI_IO_3	LPC Multiplexed Command, Addr & Data 3	I/O-3.3	-
B8	LPC_DRQ0#/ESPI_ALERT0#	LPC Serial DMA/Master Request 0	NC	Not supported
B9	LPC_DRQ1#/ESPI_ALERT1#	LPC Serial DMA/Master Request 1	NC	Not supported
B10	LPC_CLK/ESPI_CLK	24MHz LPC clock	O-3.3	-
B11	GND	Power Ground	PWR GND	-
B12	PWRBTN#	Power Button	I-3.3	PU 10k 3.3V (S5)
B13	SMB_CLK	SMBUS Clock	O-3.3	PU 3k3 3.3V (S5)
B14	SMB_DAT	SMBUS Data	I/O-3.3	PU 3k3 3.3V (S5)
B15	SMB_ALERT#	SMBUS Alert	I/O-3.3	PU 3k3 3.3V (S5)
B16	SATA1_TX+	SATA 1 Transmit Pair +	DP-O	AC Coupled on Module
B17	SATA1_TX-	SATA 1 Transmit Pair -	DP-O	AC Coupled on Module
B18	SUS_STAT#/ESPI_RESE T#	Suspend Status	O-3.3	PD 10k
B19	SATA1_RX+	SATA 1 Receive Pair +	DP-I	AC Coupled on Module
B20	SATA1_RX-	SATA 1 Receive Pair -	DP-I	AC Coupled on Module
B21	GND	Power Ground	PWR GND	-
B22	PCIE_RX15+	PCI Express Lane 15 Receive +	DP-I	-
B23	PCIE_RX15-	PCI Express Lane 15 Receive -	DP-I	-
B24	PWR_OK	Power OK	I-3.3	PU 51K (S5) via diode
B25	PCIE_RX14+	PCI Express Lane 14 Receive +	DP-I	-
B26	PCIE_RX14-	PCI Express Lane 14 Receive -	DP-I	-
B27	WDT	Watch Dog Time-Out event	O-3.3	PD 10K
B28	R3.0: RSVD	Reserved for future use	NC	-
	R3.1: GND	Power Ground	PWR GND	-
B29	R3.0: RSVD	Reserved for future use	NC	-
	R3.1: PCIE1_CLK_REF+	Reference PCI Express Clock+	DP-O	100MHz, for PCIe 4.0 on Lanes 16 to 31
B30	R3.0: RSVD	Reserved for future use	NC	-
	R3.1: PCIE1_CLK_REF-	Reference PCI Express Clock-	DP-O	100MHz, for PCIe 4.0 on Lanes 16 to 31
B31	GND	Power Ground	PWR GND	-
B32	SPKR	Speaker	O-3.3	From FPGA
B33	I2C_CLK	I2C Clock	O-3.3	PU 2k2 3.3V (S5)
B34	I2C_DAT	I2C Data	I/O-3.3	PU 2k2 3.3V (S5)
B35	THRM#	Over Temperature Input	I-3.3	PU 10k 3.3V (S0)

Pin	Signal	Description	Type	Termination / Comment
B36	PCIE_RX13+	PCI Express Lane 13 Receive +	DP-I	-
B37	PCIE_RX13-	PCI Express Lane 13 Receive -	DP-I	-
B38	GND	Power Ground	PWR GND	-
B39	PCIE_RX12+	PCI Express Lane 12 Receive +	DP-I	-
B40	PCIE_RX12-	PCI Express Lane 12 Receive -	DP-I	-
B41	GND	Power Ground	PWR GND	-
B42	USB3-	USB 2.0 Data Pair Port 3 -	DP-I/O	-
B43	USB3+	USB 2.0 Data Pair Port 3 +	DP-I/O	-
B44	USB_0_1_OC#	USB Overcurrent Indicator Port 0/1	I-3.3	PU 10k 3.3V (S5)
B45	USB1-	USB 2.0 Data Pair Port 1 -	DP-I/O	-
B46	USB1+	USB 2.0 Data Pair Port 1 +	DP-I/O	-
B47	ESPI_EN#	LPC/eSPI mode selection	NC	PU 20k 3.3V (S5); Not supported
B48	USB0_HOST_PRSENT	USB host presence on USB0	NC	Not supported
B49	SYS_RESET#	Reset Button Input	I-3.3	PU 10k 3.3V (S5)
B50	CB_RESET#	Carrier Board Reset	O-3.3	-
B51	GND	Power Ground	PWR GND	-
B52	PCIE_RX5+	PCI Express Lane 5 Receive +	DP-I	-
B53	PCIE_RX5-	PCI Express Lane 5 Receive -	DP-I	-
B54	GPO1	General Purpose Output 1	O-3.3	PD 100k
B55	PCIE_RX4+	PCI Express Lane 4 Receive +	DP-I	-
B56	PCIE_RX4-	PCI Express Lane 4 Receive -	DP-I	-
B57	GPO2	General Purpose Output 2	O-3.3	PD 100k
B58	PCIE_RX3+	PCI Express Lane 3 Receive +	DP-I	-
B59	PCIE_RX3-	PCI Express Lane 3 Receive -	DP-I	-
B60	GND	Power Ground	PWR GND	-
B61	PCIE_RX2+	PCI Express Lane 2 Receive +	DP-I	-
B62	PCIE_RX2-	PCI Express Lane 2 Receive -	DP-I	-
B63	GPO3	General Purpose Output 3	O-3.3	PD 100k
B64	PCIE_RX1+	PCI Express Lane 1 Receive +	DP-I	-
B65	PCIE_RX1-	PCI Express Lane 1 Receive -	DP-I	-
B66	WAKE0#	PCI Express Wake Event	I-3.3	PU 10k 3.3V (S5)
B67	WAKE1#	General Purpose Wake Event	I-3.3	PU 10k 3.3V (S5)
B68	PCIE_RX0+	PCI Express Lane 0 Receive +	DP-I	-
B69	PCIE_RX0-	PCI Express Lane 0 Receive -	DP-I	-

Pin	Signal	Description	Type	Termination / Comment
B70	GND	Power Ground	PWR GND	-
B71	PCIE_RX8+	PCI Express Lane 8 Receive +	DP-I	-
B72	PCIE_RX8-	PCI Express Lane 8 Receive -	DP-I	-
B73	GND	Power Ground	PWR GND	-
B74	PCIE_RX9+	PCI Express Lane 9 Receive +	DP-I	-
B75	PCIE_RX9-	PCI Express Lane 9 Receive -	DP-I	-
B76	GND	Power Ground	PWR GND	-
B77	PCIE_RX10+	PCI Express Lane 10 Receive +	DP-I	-
B78	PCIE_RX10-	PCI Express Lane 10 Receive -	DP-I	-
B79	GND	Power Ground	PWR GND	-
B80	GND	Power Ground	PWR GND	-
B81	PCIE_RX11+	PCI Express Lane 11 Receive +	DP-I	-
B82	PCIE_RX11-	PCI Express Lane 11 Receive -	DP-I	-
B83	GND	Power Ground	PWR GND	-
B84	VCC_5V_SBY	5V Standby	PWR 5V (S5)	optional (not necessary in single supply mode)
B85	VCC_5V_SBY	5V Standby	PWR 5V (S5)	optional (not necessary in single supply mode)
B86	VCC_5V_SBY	5V Standby	PWR 5V (S5)	optional (not necessary in single supply mode)
B87	VCC_5V_SBY	5V Standby	PWR 5V (S5)	optional (not necessary in single supply mode)
B88	BIOS_DIS1#	BIOS Selection Strap 1	I-3.3	PU 10k 3.3V (S5)
B89	NCSI_RX_ER	NC-SI Receive error	O-3.3	PD 10k DNI
B90	GND	Power Ground	PWR GND	-
B91	NCSI_CLK_IN	NC-SI Clock	I-3.3	PD 10k
B92	NCSI_RXD1	NC-SI Receive Data	O-3.3	-
B93	NCSI_RXD0	NC-SI Receive Data	O-3.3	-
B94	NCSI_CRS_DV	NC-SI Carrier Sense/Receive Data Valid	O-3.3	-
B95	NCSI_TXD1	NC-SI Transmit Data	I-3.3	PD 10k
B96	NCSI_TXD0	NC-SI Transmit Data	I-3.3	PD 10k
B97	SPI_CS#	SPI Chip Select	O-3.3	PU 4k7 (SPI)
B98	NCSI_ARB_IN	NC-SI hardware arbitration input	I-3.3	PD 10k
B99	NCSI_ARB_OUT	NC-SI hardware arbitration output	O-3.3	PU 10k 3.3V (S5)
B100	GND	Power Ground	PWR GND	-

Pin	Signal	Description	Type	Termination / Comment
B101	FAN_PWMOUT	Fan PWM Output	O-3.3	20V protection circuit implemented on module, PD on carrier needed for proper operation
B102	FAN_TACHIN	Fan Tach Input	I-3.3	PU 47k 3.3V (S0); 20V protection circuit implemented on module
B103	SLEEP#	Sleep Button Input	I-3.3	PU 47k 3.3V (S5); 20V protection circuit implemented on module
B104	VCC_12V	Main Input Voltage	PWR	-
B105	VCC_12V	Main Input Voltage	PWR	-
B106	VCC_12V	Main Input Voltage	PWR	-
B107	VCC_12V	Main Input Voltage	PWR	-
B108	VCC_12V	Main Input Voltage	PWR	-
B109	VCC_12V	Main Input Voltage	PWR	-
B110	GND	Power Ground	PWR GND	-

Table 29: Pin-out List C

Pin	Signal	Description	Type	Termination / Comment
C1	GND	Power Ground	PWR GND	-
C2	GND	Power Ground	PWR GND	-
C3	USB_SSRX0-	USB Super Speed Receive – (0)	DP-I	-
C4	USB_SSRX0+	USB Super Speed Receive + (0)	DP-I	-
C5	GND	Power Ground	PWR GND	-
C6	USB_SSRX1-	USB Super Speed Receive – (1)	DP-I	-
C7	USB_SSRX1+	USB Super Speed Receive + (1)	DP-I	-
C8	GND	Power Ground	PWR GND	-
C9	USB_SSRX2-	USB Super Speed Receive – (2)	DP-I	-
C10	USB_SSRX2+	USB Super Speed Receive + (2)	DP-I	-
C11	GND	Power Ground	PWR GND	-
C12	USB_SSRX3-	USB Super Speed Receive – (3)	DP-I	-
C13	USB_SSRX3+	USB Super Speed Receive + (3)	DP-I	-
C14	GND	Power Ground	PWR GND	-
C15	R3.0: 10G_PHY_MDC_SCL3	Management I2C Clock for external PHY	O/OD-3.3	PU 2k2 3.3V (S5)
	R3.1: RSVD10G	Not used	NC	-
C16	R3.0: 10G_PHY_MDC_SCL2	Management I2C Clock for external PHY	O/OD-3.3	PU 2k2 3.3V (S5)
	R3.1: RSVD10G	Not used	NC	-
C17	10G_SDP2	Software-Definable Pin	I/O-3.3	-
C18	GND	Power Ground	PWR GND	-
C19	PCIE_RX6+	PCI Express Lane 6 Receive +	DP-I	-
C20	PCIE_RX6-	PCI Express Lane 6 Receive -	DP-I	-
C21	GND	Power Ground	PWR GND	-
C22	PCIE_RX7+	PCI Express Lane 7 Receive +	DP-I	-
C23	PCIE_RX7-	PCI Express Lane 7 Receive -	DP-I	-
C24	R3.0: 10G_INT2	Interrupt from copper PHY or optical SFP Module	I-3.3	PU 2k2 3.3V (S5)
	R3. 1: RSVD10G	Not used	NC	-
C25	GND	Power Ground	PWR GND	-
C26	10G_KR_RX3+	10GBASE-KR receive differential pair +	DP-I	AC Coupled on Module
C27	10G_KR_RX3-	10GBASE-KR receive differential pair -	DP-I	AC Coupled on Module
C28	GND	Power Ground	PWR GND	-

Pin	Signal	Description	Type	Termination / Comment
C29	10G_KR_RX2+	10GBASE-KR receive differential pair +	DP-I	AC Coupled on Module
C30	10G_KR_RX2-	10GBASE-KR receive differential pair -	DP-I	AC Coupled on Module
C31	GND	Power Ground	PWR GND	-
C32	R3.0: 10G_SFP_SDA3	Management I2C Data for optical SFP Module	I/O-3.3	PU 2k2 3.3V (S5)
	R3.1: RSVD10G	Not used	NC	-
C33	R3.0: 10G_SFP_SDA2	Management I2C Data for optical SFP Module	I/O-3.3	PU 2k2 3.3V (S5)
	R3.1: RSVD10G	Not used	NC	-
C34	R3.0: 10G_PHY_RST_23	Reset of optical PHY on ports 2 and 3	O-3.3	PD 10k
	R3.1: RSVD10G	Not used	NC	-
C35	R3.0: 10G_PHY_RST_01	Reset of optical PHY on ports 0 and 1	O-3.3	PD 10k
	R3.1: CEI_RST#	Reset to I/O expander on carrier		
C36	R3.0: 10G_LED_SDA	I2C Data to transfer LED signals or MDIO of opt. PHY	I/O-3.3	PU 2k2 3.3V (S5)
	R3.1: RSVD10G	Not used	NC	-
C37	R3.0: 10G_LED_SCL	I2C Clock to transfer LED signals or MDIO of opt. PHY	O-3.3	PU 2k2 3.3V (S5)
	R3.1: RSVD10G	Not used	NC	-
C38	R3.0: 10G_SFP_SDA1	Management I2C Data for optical SFP Module	I/O-3.3	PU 2k2 3.3V (S5)
	R3.1: RSVD10G	Not used	NC	-
C39	R3.0: 10G_SFP_SDA0	Management I2C Data for optical SFP Module	I/O-3.3	PU 2k2 3.3V (S5)
	R3.1: CEI_SDA	I2C data – for SFP setup		PU 10k 3.3V (S5)
C40	10G_SDPO	Software-Definable Pin	I/O-3.3	-
C41	GND	Power Ground	PWR GND	-
C42	10G_KR_RX1+	10GBASE-KR receive differential pair +	DP-I	AC Coupled on Module
C43	10G_KR_RX1-	10GBASE-KR receive differential pair -	DP-I	AC Coupled on Module
C44	GND	Power Ground	PWR GND	-
C45	R3.0: 10G_PHY_MDC_SCL1	Management I2C Clock for external PHY	O/OD-3.3	PU 2k2 3.3V (S5)
	R3.1: RSVD10G	Not used	NC	-
C46	R3.0: 10G_PHY_MDC_SCL0	MDIO clock - for PHY setup	O/OD-3.3	PU 2k2 3.3V (S5)

Pin	Signal	Description	Type	Termination / Comment
	R3.1: CEI_MDC			PU 1k 3.3V (S5)
C47	R3.0: 10G_INT0	Interrupt from copper PHY or optical SFP Module	I-3.3	PU 2k2 3.3V (S5)
	R3.1: CEI_INT#	Interrupt from external I2C I/O expander		PU 10k 3.3V (S5)
C48	GND	Power Ground	PWR GND	-
C49	10G_KR_RX0+	10GBASE-KR receive differential pair +	DP-I	AC Coupled on Module
C50	10G_KR_RX0-	10GBASE-KR receive differential pair -	DP-I	AC Coupled on Module
C51	GND	Power Ground	PWR GND	-
C52	PCIE_RX16+	PCI Express Lane 16 Receive +	DP-I	-
C53	PCIE_RX16-	PCI Express Lane 16 Receive -	DP-I	-
C54	TYPE0#	GND for type 7 module	GND	-
C55	PCIE_RX17+	PCI Express Lane 17 Receive +	DP-I	-
C56	PCIE_RX17-	PCI Express Lane 17 Receive -	DP-I	-
C57	TYPE1#	NC for type 7 module	NC	-
C58	PCIE_RX18+	PCI Express Lane 18 Receive +	DP-I	-
C59	PCIE_RX18-	PCI Express Lane 18 Receive -	DP-I	-
C60	GND	Power Ground	PWR GND	-
C61	PCIE_RX19+	PCI Express Lane 19 Receive +	DP-I	-
C62	PCIE_RX19-	PCI Express Lane 19 Receive -	DP-I	-
C63	RSVD	Reserved for future use	NC	-
C64	RSVD	Reserved for future use	NC	-
C65	PCIE_RX20+	PCI Express Lane 20 Receive +	DP-I	-
C66	PCIE_RX20-	PCI Express Lane 20 Receive -	DP-I	-
C67	RAPID_SHUTDOWN	Trigger for Rapid Shutdown	I-5.0	PD 100k
C68	PCIE_RX21+	PCI Express Lane 21 Receive +	DP-I	-
C69	PCIE_RX21-	PCI Express Lane 21 Receive -	DP-I	-
C70	GND	Power Ground	PWR GND	-
C71	PCIE_RX22+	PCI Express Lane 22 Receive +	DP-I	-
C72	PCIE_RX22-	PCI Express Lane 22 Receive -	DP-I	-
C73	GND	Power Ground	PWR GND	-
C74	PCIE_RX23+	PCI Express Lane 23 Receive +	DP-I	-
C75	PCIE_RX23-	PCI Express Lane 23 Receive -	DP-I	-
C76	GND	Power Ground	PWR GND	-
C77	RSVD	Reserved for future use	NC	-

Pin	Signal	Description	Type	Termination / Comment
C78	PCIE_RX24+	PCI Express Lane 24 Receive +	DP-I	-
C79	PCIE_RX24-	PCI Express Lane 24 Receive -	DP-I	-
C80	GND	Power Ground	PWR GND	-
C81	PCIE_RX25+	PCI Express Lane 25 Receive +	DP-I	-
C82	PCIE_RX25-	PCI Express Lane 25 Receive -	DP-I	-
C83	RSVD	Reserved for future use	NC	-
C84	GND	Power Ground	PWR GND	-
C85	PCIE_RX26+	PCI Express Lane 26 Receive +	DP-I	-
C86	PCIE_RX26-	PCI Express Lane 26 Receive -	DP-I	-
C87	GND	Power Ground	PWR GND	-
C88	PCIE_RX27+	PCI Express Lane 27 Receive +	DP-I	-
C89	PCIE_RX27-	PCI Express Lane 27 Receive -	DP-I	-
C90	GND	Power Ground	PWR GND	-
C91	PCIE_RX28+	PCI Express Lane 28 Receive +	DP-I	-
C92	PCIE_RX28-	PCI Express Lane 28 Receive -	DP-I	-
C93	GND	Power Ground	PWR GND	-
C94	PCIE_RX29+	PCI Express Lane 29 Receive +	DP-I	-
C95	PCIE_RX29-	PCI Express Lane 29 Receive -	DP-I	-
C96	GND	Power Ground	PWR GND	-
C97	RSVD	Reserved for future use	NC	-
C98	PCIE_RX30+	PCI Express Lane 30 Receive +	DP-I	-
C99	PCIE_RX30-	PCI Express Lane 30 Receive -	DP-I	-
C100	GND	Power Ground	PWR GND	-
C101	PCIE_RX31+	PCI Express Lane 31 Receive +	DP-I	-
C102	PCIE_RX31-	PCI Express Lane 31 Receive -	DP-I	-
C103	GND	Power Ground	PWR GND	-
C104	VCC_12V	Main Input Voltage	PWR	-
C105	VCC_12V	Main Input Voltage	PWR	-
C106	VCC_12V	Main Input Voltage	PWR	-
C107	VCC_12V	Main Input Voltage	PWR	-
C108	VCC_12V	Main Input Voltage	PWR	-
C109	VCC_12V	Main Input Voltage	PWR	-
C110	GND	Power Ground	PWR GND	-

Table 30: Pin-out List D

Pin	Signal	Description	Type	Termination / Comment
D1	GND	Power Ground	PWR GND	-
D2	GND	Power Ground	PWR GND	-
D3	USB_SSTX0-	USB Super Speed Transmit – (0)	DP-O	-
D4	USB_SSTX0+	USB Super Speed Transmit + (0)	DP-O	-
D5	GND	Power Ground	PWR GND	-
D6	USB_SSTX1-	USB Super Speed Transmit – (1)	DP-O	-
D7	USB_SSTX1+	USB Super Speed Transmit + (1)	DP-O	-
D8	GND	Power Ground	PWR GND	-
D9	USB_SSTX2-	USB Super Speed Transmit – (2)	DP-O	-
D10	USB_SSTX2+	USB Super Speed Transmit + (2)	DP-O	-
D11	GND	Power Ground	PWR GND	-
D12	USB_SSTX3-	USB Super Speed Transmit – (3)	DP-O	-
D13	USB_SSTX3+	USB Super Speed Transmit + (3)	DP-O	-
D14	GND	Power Ground	PWR GND	-
D15	R3.0: 10G_PHY_MDIO_SDA3	Management I2C Data for external PHY	I/O-3.3	PU 2k2 3.3V (S5)
	R3.1: RSVD10G	Not used	NC	-
D16	R3.0: 10G_PHY_MDIO_SDA2	Management I2C Data for external PHY	I/O-3.3	PU 2k2 3.3V (S5)
	R3.1: RSVD10G	Not used	NC	-
D17	10G_SDP3	Software-Definable Pin	I/O-3.3	-
D18	GND	Power Ground	PWR GND	-
D19	PCIE_TX6+	PCI Express Lane 6 Transmit +	DP-O	AC Coupled on Module
D20	PCIE_TX6-	PCI Express Lane 6 Transmit -	DP-O	AC Coupled on Module
D21	GND	Power Ground	PWR GND	-
D22	PCIE_TX7+	PCI Express Lane 7 Transmit +	DP-O	AC Coupled on Module
D23	PCIE_TX7-	PCI Express Lane 7 Transmit -	DP-O	AC Coupled on Module
D24	R3.0: 10G_INT3	Interrupt From copper PHY or optical SFP Module	I-3.3	PU 2k2 3.3V (S5)
	R3.1: RSVD10G	Not used	NC	-
D25	GND	Power Ground	PWR GND	-
D26	10G_KR_TX3+	10GBASE-KR Transmit +	DP-O	-
D27	10G_KR_TX3-	10GBASE-KR Transmit -	DP-O	-
D28	GND	Power Ground	PWR GND	-
D29	10G_KR_TX2+	10GBASE-KR Transmit +	DP-O	-

Pin	Signal	Description	Type	Termination / Comment
D30	10G_KR_TX2-	10GBASE-KR Transmit -	DP-O	-
D31	GND	Power Ground	PWR GND	-
D32	R3.0: 10G_SFP_SCL3	Management I2C Clock for optical SFP Module	I/O-3.3	PU 2k2 3.3V (S5)
	R3.1: RSVD10G	Not used	NC	-
D33	R3.0: 10G_SFP_SCL2	Management I2C Clock for optical SFP Module	I/O-3.3	PU 2k2 3.3V (S5)
	R3.1: RSVD10G	Not used	NC	-
D34	R3.0: 10G_PHY_CAP_23	PHY on ports 2 and 3 mode capability – I2C or MDIO	I-3.3	PU 10k 3.3V (S5)
	R3.1: RSVD10G	Not used	NC	-
D35	R3.0: 10G_PHY_CAP_01	PHY on ports 0 and 1 mode capability – I2C or MDIO	I-3.3	PU 10k 3.3V (S5)
	R3.1: CEI_PRSENT#	Presence of CEI compliant hardware		
D36	RSVD	Reserved for future use	NC	-
D37	RSVD	Reserved for future use	NC	-
D38	R3.0: 10G_SFP_SCL1	Management I2C Clock for optical SFP Module	I/O-3.3	PU 2k2 3.3V (S5)
	R3.1: RSVD10G	Not used	NC	-
D39	R3.0: 10G_SFP_SCL0	Management I2C Clock for optical SFP Module	I/O-3.3	PU 2k2 3.3V (S5)
	R3.1: CEI_SCL	I2C clock for CEI I2C port		PU 10k 3.3V (S5)
D40	10G_SDP1	Software-Definable Pin	I/O-3.3	-
D41	GND	Power Ground	PWR GND	-
D42	10G_KR_TX1+	10GBASE-KR Transmit +	DP-O	-
D43	10G_KR_TX1-	10GBASE-KR Transmit -	DP-O	-
D44	GND	Power Ground	PWR GND	-
D45	R3.0: 10G_PHY_MDIO_SDA1	Management I2C Data for external PHY	I/O-3.3	PU 2k2 3.3V (S5)
	R3.1: RSVD10G	Not used	NC	-
D46	R3.0: 10G_PHY_MDIO_SDA0	MDIO data – for external PHY setup	I/O-3.3	PU 2k2 3.3V (S5)
	R3.1: CEI_MDIO			PU 1k 3.3V (S5)
D47	R3.0: 10G_INT1	Interrupt from copper PHY or optical SFP Module	I-3.3	PU 2k2 3.3V (S5)
	R3.1: ETH_PHY_INT#	Interrupt from external I2C I/O expander		PU 2k 3.3V (S5)
D48	GND	Power Ground	PWR GND	-
D49	10G_KR_TX0+	10GBASE-KR Transmit +	DP-O	-
D50	10G_KR_TX0-	10GBASE-KR Transmit -	DP-O	-

Pin	Signal	Description	Type	Termination / Comment
D51	GND	Power Ground	PWR GND	-
D52	PCIE_TX16+	PCI Express Lane 16 Transmit +	DP-O	AC Coupled on Module
D53	PCIE_TX16-	PCI Express Lane 16 Transmit -	DP-O	AC Coupled on Module
D54	RSVD	Reserved for future use	NC	-
D55	PCIE_TX17+	PCI Express Lane 17 Transmit +	DP-O	AC Coupled on Module
D56	PCIE_TX17-	PCI Express Lane 17 Transmit -	DP-O	AC Coupled on Module
D57	TYPE2#	GND for type 7 module	GND	-
D58	PCIE_TX18+	PCI Express Lane 18 Transmit +	DP-O	AC Coupled on Module
D59	PCIE_TX18-	PCI Express Lane 18 Transmit -	DP-O	AC Coupled on Module
D60	GND	Power Ground	PWR GND	-
D61	PCIE_TX19+	PCI Express Lane 19 Transmit +	DP-O	AC Coupled on Module
D62	PCIE_TX19-	PCI Express Lane 19 Transmit -	DP-O	AC Coupled on Module
D63	RSVD	Reserved for future use	NC	-
D64	RSVD	Reserved for future use	NC	-
D65	PCIE_TX20+	PCI Express Lane 20 Transmit +	DP-O	AC Coupled on Module
D66	PCIE_TX20-	PCI Express Lane 20 Transmit -	DP-O	AC Coupled on Module
D67	GND	Power Ground	PWR GND	-
D68	PCIE_TX21+	PCI Express Lane 21 Transmit +	DP-O	AC Coupled on Module
D69	PCIE_TX21-	PCI Express Lane 21 Transmit -	DP-O	AC Coupled on Module
D70	GND	Power Ground	PWR GND	-
D71	PCIE_TX22+	PCI Express Lane 22 Transmit +	DP-O	AC Coupled on Module
D72	PCIE_TX22-	PCI Express Lane 22 Transmit -	DP-O	AC Coupled on Module
D73	GND	Power Ground	PWR GND	-
D74	PCIE_TX23+	PCI Express Lane 23 Transmit +	DP-O	AC Coupled on Module
D75	PCIE_TX23-	PCI Express Lane 23 Transmit -	DP-O	AC Coupled on Module
D76	GND	Power Ground	PWR GND	-
D77	RSVD	Reserved for future use	NC	-
D78	PCIE_TX24+	PCI Express Lane 24 Transmit +	DP-O	AC Coupled on Module
D79	PCIE_TX24-	PCI Express Lane 24 Transmit -	DP-O	AC Coupled on Module
D80	GND	Power Ground	PWR GND	-
D81	PCIE_TX25+	PCI Express Lane 25 Transmit +	DP-O	AC Coupled on Module
D82	PCIE_TX25-	PCI Express Lane 25 Transmit -	DP-O	AC Coupled on Module
D83	RSVD	Reserved for future use	NC	-
D84	GND	Power Ground	PWR GND	-
D85	PCIE_TX26+	PCI Express Lane 26 Transmit +	DP-O	AC Coupled on Module

Pin	Signal	Description	Type	Termination / Comment
D86	PCIE_TX26-	PCI Express Lane 26 Transmit -	DP-O	AC Coupled on Module
D87	GND	Power Ground	PWR GND	-
D88	PCIE_TX27+	PCI Express Lane 27 Transmit +	DP-O	AC Coupled on Module
D89	PCIE_TX27-	PCI Express Lane 27 Transmit -	DP-O	AC Coupled on Module
D90	GND	Power Ground	PWR GND	-
D91	PCIE_TX28+	PCI Express Lane 28 Transmit +	DP-O	AC Coupled on Module
D92	PCIE_TX28-	PCI Express Lane 28 Transmit -	DP-O	AC Coupled on Module
D93	GND	Power Ground	PWR GND	-
D94	PCIE_TX29+	PCI Express Lane 29 Transmit +	DP-O	AC Coupled on Module
D95	PCIE_TX29-	PCI Express Lane 29 Transmit -	DP-O	AC Coupled on Module
D96	GND	Power Ground	PWR GND	-
D97	RSVD	Reserved for future use	NC	-
D98	PCIE_TX30+	PCI Express Lane 30 Transmit +	DP-O	AC Coupled on Module
D99	PCIE_TX30-	PCI Express Lane 30 Transmit -	DP-O	AC Coupled on Module
D100	GND	Power Ground	PWR GND	-
D101	PCIE_TX31+	PCI Express Lane 31 Transmit +	DP-O	AC Coupled on Module
D102	PCIE_TX31-	PCI Express Lane 31 Transmit -	DP-O	AC Coupled on Module
D103	GND	Power Ground	PWR GND	-
D104	VCC_12V	Main Input Voltage	PWR	-
D105	VCC_12V	Main Input Voltage	PWR	-
D106	VCC_12V	Main Input Voltage	PWR	-
D107	VCC_12V	Main Input Voltage	PWR	-
D108	VCC_12V	Main Input Voltage	PWR	-
D109	VCC_12V	Main Input Voltage	PWR	-
D110	GND	Power Ground	PWR GND	-

Table 31: Summary – COM.0 REV3.1 vs REV3.0

REV3.1	REV 3.1 Description	REV3.0	Pin
GBE0_LINK_MID#	Gigabit Ethernet Controller MID Speed Link indicator	GBE0_LINK_100#	A4
GBE0_LINK_MAX#	Gigabit Ethernet Controller MAX Speed Link indicator	GBE0_LINK_1000#	A5
PCIE1_CK_REF+ PCIE1_CK_REF-	Second reference clock output for higher speed PCI Express implementation on Lanes 16 to 31	Reserved pins	B29 B30
CEI_MDIO	MDIO data – for PHY setup	10G_PHY_MDIO_SDA0	D46
CEI_MDC	MDIO clock - for PHY setup	10G_PHY_MDC_SCL0	C46

REV3.1	REV 3.1 Description	REV3.0	Pin
CEI_SDA	I2C data – for SFP setup, serialized status LEDs and miscellaneous serialized signals	10G_SFP_SDA0	C39
CEI_SCL	I2C clock for CEI I2C port	10G_SFP_SCL0	D39
CEI_INT#	Active low interrupt input to Module from Carrier based I2C I/O expander	10G_INT0	C47
ETH_PHY_INT#	Second active low interrupt input to Module from Carrier based I2C I/O expander	10G_INT1	D47
CEI_RST#	Active low reset output from Module to Carrier based I/O expander	10G_PHY_RST_01	C35
CEI_PRSENT#	Input signal from Carrier indicating presence of CEI compliant hardware on the Carrier	10G_PHY_CAP_01	D35
Reserved pin	Not used	10G_PHY_RST_23	C34
Reserved pin	Not used	10G_PHY_CAP_23	D34
Reserved pins	Not used	10G_PHY_MDIO_SDA[1:3]	D45, D16, D15
Reserved pins	Not used	10G_PHY_MDC_SCL[1:3]	C45, C16, C15
Reserved pins	Not used	10G_SFP_SDA[1:3]	C38, C33, C32
Reserved pins	Not used	10G_SFP_SCL[1:3]	D38, D33, D32
Reserved pin	Not used	10G_LED_SDA	C36
Reserved pin	Not used	10G_LED_SCL	C37
Reserved pins	Not used	10G_INT[2:3]	C24, D24

11/ UEFI BIOS

11.1. Starting the UEFI BIOS

The COMe-bID710 (E2) uses a JUMPTec-customized, pre-installed and configured version of AMI Aptio® V BIOS based on the Unified Extensible Firmware Interface (UEFI) specification and the Intel® Platform Innovation Framework for EFI.

The UEFI BIOS provides a variety of new and enhanced functions specifically tailored to the hardware features of the COMe-bID7 (E2).



This chapter provides an overview of the BIOS and its setup. A more detailed listing and description of all BIOS setup nodes can be found in the BIOS file package available on our [Customer Section](#). Please register there to get access to BIOS downloads and Product Change Notifications.

The UEFI BIOS comes with a Setup program that provides quick and easy access to the individual function settings for control or modification of the default configuration. The Setup program allows access to various menus resp. sub-menus that provide the specific functions.

To start the UEFI BIOS Setup program, follow the steps below:

1. Power on the board
2. Wait until the first characters appear on the screen (POST messages or splash screen)
3. Press the key
4. If the UEFI BIOS is password-protected, a request for password will appear. Enter either the User Password or the Supervisor Password (see Security Setup Menu), press <RETURN>, and proceed with step 5.
5. The Setup menu appears

11.2. Navigating the UEFI BIOS

The COMe-bID7 (E2) UEFI BIOS Setup program uses a hot key navigation system. The hot key legend bar is located at the bottom of the Setup screens. The following table provides a list of navigation hot keys available in the legend bar.

Table 32: Navigation Hot Keys Available in the Legend Bar

Sub-screen	Description
<F1>	<F1> key invokes the General Help window
<->	<Minus> key selects the next lower value within a field
<+>	<Plus> key selects the next higher value within a field
<F2>	<F2> key loads previous values
<F3>	<F3> key loads optimized defaults
<F4>	<F4> key Saves and Exits
<-> or <↔>	<Left/Right> arrows selects major Setup menus on menu bar, for example, Main or Advanced

Sub-screen	Description
<↑> or <↓>	<Up/Down> arrows select fields in the current menu, for example, Setup function or sub-screen
<ESC>	<ESC> key exits a major Setup menu and enters the Exit Setup menu Pressing the <ESC> key in a sub-menu displays the next higher menu level
<RETURN>	<RETURN> key executes a command or selects a submenu

11.3. Setup Menus

The Setup utility features a selection bar at the top of the screen that lists the menus.



Figure 12: Setup Menu Selection Bar

The Setup menus available for the COMe-bID7 are:

- › Main
- › Advanced
- › PlatformConfiguration
- › Socket Configuration
- › Security
- › Boot
- › Save & Exit

The currently active menu and the currently active UEFI BIOS Setup item are highlighted in white. Use the left and right arrow keys to select the Setup menus.

Each Setup menu provides two main frames. The left frame displays all available functions. Configurable functions are displayed in blue. Functions displayed in grey provide information about the status or the operational configuration.

11.4. Getting Help

The right frame displays a Help window providing an explanation of the respective function.

11.5. UEFI Shell

The JUMPTec UEFI BIOS features a built-in and enhanced version of the UEFI Shell. For a detailed description of the available standard shell scripting, refer to the EFI Shell User Guide. For a detailed description of the available standard shell commands, refer to the EFI Shell Command Manual. Both documents can be downloaded from the EFI and Framework Open Source Community homepage:

<http://sourceforge.net/projects/efi-shell/files/documents/>



JUMPTec UEFI BIOS does not provide all shell commands described in the EFI Shell Command Manual.

11.5.1. Entering the UEFI Shell

To enter the UEFI Shell, follow the steps below:

1. Power on the board
2. Press the <F7> key (instead of) to display a choice of boot devices
3. Select 'UEFI: Built-in EFI shell'

```
UEFI Interactive Shell v2.2
EDK II / JUMPTec add-on v0.3
UEFI v2.80 (American Megatrends, 0x0005001A)
map: No mapping found.
```

4. Press the <ESC> key within 5 seconds to skip startup.nsh or any other key to continue
The output produced by the device-mapping table can vary depending on the board's configuration
If the <ESC> key is pressed before the 5 second timeout elapses, the shell prompt is shown:

```
Shell>
```

11.5.2. Exiting the UEFI Shell

To exit the UEFI Shell, follow one of the steps below:

- Use the *exit* UEFI Shell command to select the boot device, in the Boot menu, that the OS boots from
- Reset the board using the *reset* UEFI Shell command
- Press the reset button of the board or power down/up the board

11.6. UEFI Shell Scripting

11.6.1. Startup Scripting

If the <ESC key is not pressed and the timeout has run out then the UEFI Shell automatically tries to execute some startup scripts. It searches for scripts and executes them in the following order:

1. Initially searches for JUMPTec flash-stored startup script.
2. If there is no JUMPTec flash-stored startup script present, then the UEFI-specified **startup.nsh** script is used. This script must be located on the root of any of the attached FAT formatted disk drive.
3. If none of the startup scripts are present or the startup script terminates then the default boot order is continued.

11.6.2. Create a Startup Script

Startup scripts can be created using the UEFI Shell built-in editor **edit** or under any OS with a plain text editor of your choice.

11.6.3. Example of Startup Scripts

Execute Shell Script on other Harddrive

This example (**startup.nsh**) executes the shell script named **bootme.nsh** located in the root of the first detected disk drive (**fs0**).

```
fs0:  
bootme.nsh
```

11.7. Firmware Update

Firmware updates are typically delivered as a ZIP archive. Please find the latest available BIOS-ZIP archive on JUMPTec's [Customer Section](#). Further information about the firmware update procedure can be found in the included "flash_instruction.txt"-file.



Register to JUMPTec's [Customer Section](#) to get access to BIOS downloads, additional documentation and Product Change Notification service.

12/ Technical Support

For technical support contact our Support Department:

- › E-mail: techsupport@jumptec.com

Make sure you have the following information available when you call:

- › Product ID Number (P/N),
- › Serial Number (SN) Module's revision
- › Operating System and Kernel/Build version
- › Software modifications
- › Additional connected hardware/full description of hardware set up



The serial number can be found on the Type Label, located on the product's rear panel.

Be ready to explain the nature of your problem to the service technician.

12.1. Warranty

Due to their limited service life, parts that by their nature are subject to a particularly high degree of wear (wearing parts) are excluded from the warranty beyond that provided by law. This applies to the lithium battery, for example.



If there is a protection label on your product, then the warranty is lost if the product is opened.

12.2. Returning Defective Merchandise

All equipment returned to JUMPTec must have a Return of Material Authorization (RMA) number assigned exclusively by JUMPTec. JUMPTec cannot be held responsible for any loss or damage caused to the equipment received without an RMA number. The buyer accepts responsibility for all freight charges for the return of goods to JUMPTec's designated facility. JUMPTec will pay the return freight charges back to the buyer's location in the event that the equipment is repaired or replaced within the stipulated warranty period. Follow these steps before returning any product to JUMPTec.

1. Visit the RMA Information website: <https://www.congatec.com/en/support/rma-information>
2. **Download the RMA Request sheet for JUMPTec GmbH and fill out the form. Take care to include a short detailed description of the observed problem or failure and to include the product identification Information (Name of product, Product number and Serial number). If a delivery includes more than one product, fill out the above information in the RMA Request form for each product.**
3. Send the completed RMA-Request form to the email address given at JUMPTec GmbH. JUMPTec will provide an RMA-Number.
4. The goods for repair must be packed properly for shipping, considering shock and ESD protection.



Goods returned to JUMPtec GmbH in non-proper packaging will be considered as customer caused faults and cannot be accepted as warranty repairs

5. Include the RMA-Number with the shipping paperwork and send the product to the delivery address provided in the RMA form or received from JUMPtec RMA Support.

13/ Storage and Transportation

13.1. Storage

If the product is not in use for an extended period time, disconnect the power plug from the power supply. If it is necessary to store the product then re-pack the product as originally delivered to avoid damage. The storage facility must meet the products environmental storage requirements as stated within this user guide. JUMPttec recommends keeping the original packaging material for future storage or warranty shipments.

13.2. Transportation

To ship the product use the original packaging, designed to withstand impact and adequately protect the product. When packing or unpacking products always take shock and ESD protection into consideration and use an EOS/ESD safe working area.

Appendix: Terminology

Term	Definition
ACPI	Advanced Configuration Power Interface – standard to implement power saving modes in PCAT systems
Basic Module	COM Express® 125mm x 95mm Module form factor.
BIOS	Basic Input Output System – firmware in PC-AT system that is used to initialize system components before handing control over to the operating system.
Carrier Board	An application specific circuit board that accepts a COM Express® Module.
Compact Module	COM Express® 95x95 Module form factor
DDI	Digital Display Interface – containing DisplayPort, HDMI/DVI and SDVO
DIMM	Dual In-line Memory Module
DRAM	Dynamic Random Access Memory
EAPI	Embedded Application Programming Interface Software interface for COM Express® specific industrial functions System information Watchdog timer I2C Bus Flat Panel brightness control User storage area GPIO
EEPROM	Electrically Erasable Programmable Read-Only Memory
Extended Module	COM Express® 155mm x 110mm Module form factor.
Gb	Gigabit
GbE	Gigabit Ethernet
GPI	General Purpose Input
GPIO	General Purpose Input Output
GPO	General Purpose Output
I2C	Inter Integrated Circuit – 2 wire (clock and data) signaling scheme allowing communication between integrated circuits, primarily used to read and load register values.
IIO	Integrated Input Output
LPC	Low Pin-Count Interface: a low speed interface used for peripheral circuits such as Super I/O controllers, which typically combine legacy-device support into a single IC.
ME	Management Engine
Mini Module	COM Express® 84x55mm Module form factor
NA	Not Available
NC	No Connect

Term	Definition
PCB	Printed Circuit Board
PCI Express PCIE	Peripheral Component Interface Express – next-generation high speed Serialized I/O bus
PEG	PCI Express Graphics
PHY	Ethernet controller physical layer device
Pin-out Type	A reference to one of seven COM Express® definitions for the signals that appear on the COM Express® Module connector pins.
RTC	Real Time Clock – battery backed circuit in PC-AT systems that keeps system time and date as well as certain system setup parameters
RP	Root Port
RPC	Root Complex
SAS	Serial Attached SCSI – high speed serial version of SCSI
SPD	Serial Presence Detect – refers to serial EEPROM on DRAMs that has DRAM Module configuration information
SPI	Serial Peripheral Interface
SO-DIMM	Small Outline Dual In-line Memory Module
S0, S1, S2, S3, S4, S5	System states describing the power and activity level S0 Full power, all devices powered S1 S2 S3 Suspend to RAM System context stored in RAM; RAM is in standby S4 Suspend to Disk System context stored on disk S5 Soft Off Main power rail off, only standby power rail present
SATA	Serial AT Attachment: serial-interface standard for hard disks
TPM	Trusted Platform Module, chip to enhance the security features of a computer system.
USB	Universal Serial Bus
WDT	Watch Dog Timer
x1	Refers to a Link or Port with one Physical Lane.
x4	Refers to a Link or Port with four Physical Lanes.
x8	Refers to a Link or Port with eight Physical Lanes.
x16	Refers to a Link or Port with sixteen Physical Lanes.



About JUMPtec

JUMPtec specializes its technical expertise in designing both - standard and highly customized compute products. Our newly optimized structure enables us to take customers from prototyping and design through to mass production faster than ever before.

JUMPtec serves a diverse range of markets, providing innovative solutions tailored to the unique needs of each industry. Find out more about our offering!

For more information, please visit: www.congatec.com

needs of each industry. Find out more about our offering!

JUMPtec GmbH

Brunnwiesenstrasse 16

94469 Deggendorf

Germany

www.congatec.com

